

MARINA II

Interior Round Pendant

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: 0-10V dimming standard with LED lamping option.


Shade: Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.



Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Cable Hung Option 5: Comes with 72" cable and cord for on-site adjustability. Canopy painted textured white.

Finish: Highly durable oven cured no VOC premium powder coat.

Modifications: Consult factory for lamping or cluster options.



SAMPLE CATALOG NUMBER:							
GL-2742-	L55-	W-	NSN-	5-	A-	072	
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
GL-2740 W in 14" mm 355 5lbs D in 9.5" mm 240 2.25kg H Specify	IN3. 3MED* L10. 1LED30 L15. 1LED35 L14. 1LED40	W White C Cream R Red BL Blue O Olive S Stone	Standard: Powder Coat Specify code from G-Lighting color chart	1. Stem 	A. No Options DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code.	Specify overall height for stem hanger option in inches.	
GL-2741 W in 18" mm 460 5lbs D in 10.5" mm 265 2.25kg H Specify	IN3. 3MED* L10. 1LED30 L15. 1LED35 L14. 1LED40	Washable: WW White WC Cream WT Tan WB Brown	Specify finish for hanger option 1 only.	5. Cord & Cable 	DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code.		
GL-2742 W in 24" mm 610 15lbs D in 11.5" mm 295 7kg H Specify	IN3. 3MED* L50. 5LED30 F4. 4CF L55. 5LED35 L54. 5LED40			Fixture painted textured white and supplied with white cord with hanger option 5.	E. Emergency Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°- 131°F. Compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.		
GL-2743 W in 30" mm 760 18lbs D in 12.5" mm 320 8kg H Specify	IN3. 3MED* L50. 5LED30 F4. 4CF L55. 5LED35 L54. 5LED40						
GL-2744 W in 36" mm 915 20lbs D in 13.5" mm 340 9kg H Specify	IN6. 6MED* L80. 8LED30 F6. 6CF L85. 8LED35 L84. 8LED40						
GL-2745 W in 48" mm 1220 25lbs D in 15.5" mm 395 11.5kg H Specify	IN6. 6MED* L80. 8LED30 F6. 6CF L85. 8LED35 L84. 8LED40						
	*120 Volt Only						

All Dimensions are nominal.

Shade

Standard

White Cream Blue Stone Red Olive

Washable - Trilam

White Tan Cream Brown

Custom fabrics available upon request. Contact factory.
Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens	Code	Lamp	Total Wattage	Delivered Lumens	Kelvin
F4,F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L50	72LED30	72W	7436	3000
IN3,IN6	MED	A-19	Medium		L55	72LED35	72W	7436	3500
					L54	72LED40	72W	7436	4000
					L80	114LED30	114W	12248	3000
					L85	114LED35	114W	12248	3500
					L84	114LED40	114W	12248	4000
Code	Lamp	Total Wattage	Delivered Lumens	Kelvin					
L10	27LED30	27 W	3008	3000					
L15	27LED35	27 W	3008	3500					
L14	27LED40	27 W	3008	4000					