

CYLINDER - QUICKSHIP

Outdoor ADA Wall Sconce

G Lighting Since 1908

9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

Fax 314.631.7800

sales@glighting.com www.glighting.com

SAMPLE CATALOG NUMBER:				
MODEL NO.	LAMPING	REFLECTOR	FINISH	OPTIONS
GL-6540 	B. LED35	Up R2 20° Fresnel Lens R3 30° Flat, Clear Lens Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens	Textured: TBL - Black TBZ - Bronze	A. No Options
GL-6541 	B. LED35	Up R5 50° Flat, Clear Lens CC Closed Cap Down R5 50° Flat, Clear Lens CC Closed Cap		
GL-6542 	B. LED35	Up R2 20° Fresnel Lens R3 30° Flat, Clear Lens Down R5 50° Flat, Clear Lens CC Closed Cap		
GL-6543 	B. LED35	Up R5 50° Flat, Clear Lens CC Closed Cap Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens		Complete LM-79 data available at glighting.com

* All dimensions are nominal.

LED	Code	Kelvin	Reflector	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
- 13W 80CRI high power LED per side	LED35	3500K	20	13	+80	50000	1231
- 0-10V dimming standard with LED lamping option			30	13	+80	50000	867
- Lumen maintenance +90% over 50,000 hour life			50	13	+80	50000	956
- Light source is field replaceable							

Mounting

- Driver mounted in 4" square by 2 1/8" deep junction box: Steel City #52171 or equivalent (supplied by others)

Driver

- Protection: electronic internal, resettable short circuit protection, thermal protection, and overload regulation
- Universal voltage 120-277 volt

Fixture is ETL listed for wet locations