

CYLINDER

Outdoor ADA Wall Sconce

| SAMPLE CATALOG NUMBER: | | | | |
|------------------------|----------------------------------|--|---|--|
| MODEL NO. | LAMPING | REFLECTOR | FINISH | OPTIONS |
| GL-6540 | C. LED30 B. LED35 E. LED40 | Up R2 20° Fresnel Lens R3 30° Flat, Clear Lens Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens | Textured: TLV - Light Verdigris TWH - White TBL - Black TS - Silver TBN - Terra Brown TBZ - Bronze Premium: SA - Satin Aluminum | A. No Options EL. Emergency Ballast <small>Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F.</small> |
| GL-6541 | C. LED30 B. LED35 E. LED40 | Up R5 50° Flat, Clear Lens CC Closed Cap Down R5 50° Flat, Clear Lens CC Closed Cap | | |
| GL-6542 | C. LED30 B. LED35 E. LED40 | Up R2 20° Fresnel Lens R3 30° Flat, Clear Lens Down R5 50° Flat, Clear Lens CC Closed Cap | | |
| GL-6543 | C. LED30 B. LED35 E. LED40 | Up R5 50° Flat, Clear Lens CC Closed Cap Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens | | |
| | | | | |

* All dimensions are nominal.

| LED | Code | Kelvin | Reflector | Total Wattage | CRI | Rated Life Hrs | Delivered Lumens |
|--|-------|--------|-----------|---------------|-----|----------------|------------------|
| - 13W 80CRI high power LED per side - 0-10V dimming standard with LED lamping option - Lumen maintenance +90% over 50,000 hour life - Light source is field replaceable | LED30 | 3000K | 20 | 13 | +80 | 50000 | 1231 |
| | | | 30 | 13 | +80 | 50000 | 867 |
| | | | 50 | 13 | +80 | 50000 | 956 |
| Mounting - Driver mounted in 4" square by 2 1/8" deep junction box: Steel City #52171 or equivalent (supplied by others) | LED35 | 3500K | 20 | 13 | +80 | 50000 | 1231 |
| | | | 30 | 13 | +80 | 50000 | 867 |
| | | | 50 | 13 | +80 | 50000 | 956 |
| Driver - Protection: electronic internal, resettable short circuit protection, thermal protection, and overload regulation - Universal voltage 120-277 volt | LED40 | 4000K | 20 | 13 | +80 | 50000 | 1231 |
| | | | 30 | 13 | +80 | 50000 | 867 |
| | | | 50 | 13 | +80 | 50000 | 956 |

Fixture is ETL listed for wet locations