

# PHOENIX

## LED Surface Mount

G Lighting Since 1908





9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

Fax 314.631.7800

sales@glighting.com www.glighting.com

SAMPLE CATALOG NUMBER: GL-6537- B- R2- TBL- A-				
MODEL NO.	LAMPING	REFLECTOR	FINISH	OPTIONS
GL-6535 	C. LED30 B. LED35 E. LED40	Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens	Textured: TLV - Light Verdigris TWH - White TBL - Black TS - Silver TBN - Terra Brown TBZ - Bronze  Premium: SA - Satin Aluminum	A. No Options EL. Emergency Ballast <small>Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F.</small>
GL-6536 	C. LED30 B. LED35 E. LED40	Down R5 50° Flat, Clear Lens		
GL-6537 	C. LED30 B. LED35 E. LED40	Down R2 20° Fresnel Lens R3 30° Flat, Clear Lens		
GL-6538 	C. LED30 B. LED35 E. LED40	Down R5 50° Flat, Clear Lens		
3" Mud Ring Required				



\* All dimensions are nominal.

LED	Code	Kelvin	Reflector	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
- 13W 80CRI high power LED - 0-10V dimming standard with LED lamping option - Lumen maintenance +90% over 50,000 hour life - Light source is field replaceable  <b>Driver</b> - Integral driver - Protection: electronic internal, resettable short circuit protection, thermal protection, and overload regulation - Universal voltage 120-277 volt - 3" mud ring must be flush or slightly recessed with a tight fit with the ceiling  <b>Mounting</b> - 4" octagon box GL-6535 - GL-6536 - 3" mud ring required for GL-6537 - GL-6538	LED30	3000K	20	13	+80	50000	1231
			30	13	+80	50000	867
			50	13	+80	50000	956
	LED35	3500K	20	13	+80	50000	1231
			30	13	+80	50000	867
			50	13	+80	50000	956
	LED40	4000K	20	13	+80	50000	1231
			30	13	+80	50000	867
			50	13	+80	50000	956

Fixture is ETL listed for dry or damp locations