

# GADSDEN

## Outdoor Sconce

**GLighting**  
Since 1908

9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000  
Fax 314.631.7800

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable.



**LED Dimming:** 0-10V dimming standard with LED lamping option.

**Body:** Spun .050 aluminum body.

**Acrylic:** UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Custom:** Contact factory for custom lamping, acrylic, or sizing.



SAMPLE CATALOG NUMBER: GL-5300-				
MODEL NO.	L15-	W-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
GL-5300 W in 6 5/8" mm 170 H in 20" mm 510 D in 8 1/2" mm 215	L10. 1LED30 L15. 1LED35 L14. 1LED40 L20. 2LED30 L25. 2LED35 L24. 2LED40	<b>Standard:</b> W. White Opal  <b>Optional:</b> S. Satin White F. Faux Alabaster M. Earth Marble <small>Acrylic is UL-94 HB Flame Class rated.</small>	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze	<b>A. No Options</b> <b>EL. Emergency LED</b> <small>Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F, LED only. Specify 120 or 277 voltage.</small>

All dimensions are nominal.

### Lamp Definition

Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
L10	14	+80	50000	1017	3000
L15	14	+80	50000	1017	3500
L14	14	+80	50000	1017	4000
L20	28	+80	50000	1992	3000
L25	28	+80	50000	1992	3500
L24	28	+80	50000	1992	4000

<sup>1</sup>Per GE lamp products catalog