

# ORBIS

## Inner Acrylic Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs.

**LED Dimming:** 0-10V dimming standard.


**Acrylic:** Acrylic is UL-94 HB Flame Class rated.

**Cable Hanger:** Standard 150" cable and white cord for on-site adjustability. Canopy painted textured white.

**Canopy:** Max remote driver installation distance: White LED 25ft from fixture body and RGB 45ft from fixture body. See Orbis Hanger Guide for more information.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**RGB:** DMX controller supplied by others.



SAMPLE CATALOG NUMBER:		F-	BLK-	1-	A
GL-2721-		LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2720</b>	W in 24" 10lbs B in 3" 4.5kg H in 11"-145"	A. 24LED30 B. 24LED35 C. 24LED40 D. RGB	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze	<b>1. Cable - Standard</b>  Drivers mounted remotely. See Orbis Hanger Guide for more information.	<b>A. No Options</b> <b>EL. Emergency LED</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. <b>BC. Black Cord</b> Fixture supplied with black power cord.
<b>GL-2736</b>	W in 36" 15lbs B in 3" 6.8kg H in 18.75"-145"	U. 36LED30 V. 36LED35 W. 36LED40 X. RGB	<b>Textured Powder</b> TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze	<b>2. Oversized</b>  Drivers mounted inside oversized canopy. See Orbis Hanger Guide for more information.	
<b>GL-2721</b>	W in 48" 15lbs B in 3" 6.8kg H in 18.75"-145"	E. 48LED30 F. 48LED35 G. 48LED40 H. RGB	<b>Premium:</b> SA-Satin Aluminum	<b>3. Vertical Remote Canopy</b>  Drivers mounted remotely. See Orbis Hanger Guide for more information.	
<b>GL-2722</b>	W in 72" 22lbs B in 3" 10kg H in 25.5"-142" Fixture Built with Four Acrylic Segments	I. 72LED30 J. 72LED35 K. 72LED40 L. RGB		<b>4. Vertical Integral Canopy</b>  Drivers mounted inside 12.5" oversized canopy. See Orbis Hanger Guide for more information.	
<b>GL-2723</b>	W in 96" 35lbs B in 3" 15.9kg H in 30.75"-139" Fixture Body Built in Four Segments and Eight Acrylic Segments.	M. 96LED30 N. 96LED35 O. 96LED40 P. RGB			
<b>GL-2724</b>	W in 120" 50lbs B in 3" 22.7kg H in 39"-133" Fixture Body Built in Three Segments and Eight Acrylic Segments	Q. 120LED30 R. 120LED35 S. 120LED40 T. RGB			

All Dimensions are nominal.

### Light Source Definition

Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
24LED30	54	+80	50000	4135	3000	72LED30	173	+80	50000	16931	3000
24LED35	54	+80	50000	4135	3500	72LED35	173	+80	50000	16931	3500
24LED40	54	+80	50000	4135	4000	72LED40	173	+80	50000	16931	4000
36LED30	76	+80	50000	7261	3000	96LED30	218	+80	50000	20604	3000
36LED35	76	+80	50000	7261	3500	96LED35	218	+80	50000	20604	3500
36LED40	76	+80	50000	7261	4000	96LED40	218	+80	50000	20604	4000
48LED30	106	+80	50000	10096	3000	120LED30	243	+80	50000	22995	3000
48LED35	106	+80	50000	10096	3500	120LED35	243	+80	50000	22995	3500
48LED40	106	+80	50000	10096	4000	120LED40	243	+80	50000	22995	4000
						RGB					

Contact Factory for Details

