

# CYLINDER - QUICKSHIP

Outdoor ADA Wall Sconce



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

SAMPLE CATALOG NUMBER:				
GL-6540-	B-	R2-R2	TBL-	A
MODEL NO.	LAMPING	REFLECTOR	FINISH	OPTIONS
<b>GL-6540</b> 	B. LED35	Up <b>R2</b> 20° Fresnel Lens <b>R3</b> 30° Flat, Clear Lens  Down <b>R2</b> 20° Fresnel Lens <b>R3</b> 30° Flat, Clear Lens	Textured: <b>TBL</b> - Black <b>TBZ</b> - Bronze	A. No Options
<b>GL-6541</b> 	B. LED35	Up <b>R5</b> 50° Flat, Clear Lens <b>CC</b> Closed Cap  Down <b>R5</b> 50° Flat, Clear Lens <b>CC</b> Closed Cap		
<b>GL-6542</b> 	B. LED35	Up <b>R2</b> 20° Fresnel Lens <b>R3</b> 30° Flat, Clear Lens  Down <b>R5</b> 50° Flat, Clear Lens <b>CC</b> Closed Cap		
<b>GL-6543</b> 	B. LED35	Up <b>R5</b> 50° Flat, Clear Lens <b>CC</b> Closed Cap  Down <b>R2</b> 20° Fresnel Lens <b>R3</b> 30° Flat, Clear Lens		

Complete LM-79 data available at [glighting.com](http://glighting.com)

\* All dimensions are nominal.

LED	— Specifications per side —						
	Code	Kelvin	Reflector	CRI	Total Wattage	Rated Life Hrs	Delivered Lumens
- 13W 80CRI high power LED per side - 0-10V dimming standard with LED lamping option - Lumen maintenance +90% over 50,000 hour life - Light source is field replaceable	LED35	3500K	20	+80	13	50000	1231
			30	+80	13	50000	867
			50	+80	13	50000	956

**Mounting**

- Driver mounted in 4" square by 2 1/8" deep junction box: Steel City #52171 or equivalent (supplied by others)

**Driver**

- Protection: electronic internal, resettable short circuit protection, thermal protection, and overload regulation
- Universal voltage 120-277 volt

Fixture is ETL listed for wet locations

