



### GENERAL SPECIFICATION

**Lamping:** Standard lamping packages offer long lamp life, high power factor energy efficient electronic ballast.

**Body:** Formed 18ga steel or .050 aluminum body.

**Acrylic:** UL-94 HB Flame Class rated.

**Standard Finishes:** Highly durable oven cured no VOC premium powder coat.

**Custom:** Contact factory for custom lamping, acrylic, or sizing.

SAMPLE CATALOG NUMBER:				
GL-4575-	B-	W-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
GL-4575 W in 8 1/2" mm 215 H in 12" mm 305 D in 4" mm 100	B. 2CFQ13 C. 2CFQ18 D. 2CFQ26	<b>Standard:</b> W. White Opal  <b>Optional:</b> S. Satin White F. Faux Alabaster M. Earth Marble 3N. Linen Cast Resin  Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat Specify code from G-Lighting color chart.	A. No Options B. Top White Perf C. Bottom White Perf E. Emergency Operates one fluorescent lamp. Remotely mounted. Specify voltage after code. Remote mount up to 5' from lamps.

All dimensions are nominal.

### Lamp Definition

Lamp	Fluorescent	Lamp Base	Rated Life Hrs	Lumens
CFQ13	CFQ 13W	GX24q-3 4-PIN	12000	900
CFQ18	CFQ 18W	GX24q-3 4-PIN	12000	1250
CFQ26	CFQ 26W	GX24q-3 4-PIN	12000	1440