

# CUBIX & APEX

## Hanger Guide























9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

**Canopy:** Max remote driver installation distance: White - 25ft from fixture body, RGB - 45ft from fixture body

### HANGER

	1. Cable (Standard)	2. Oversized	3. Vertical Remote Canopy	4. Vertical Integral Canopy
<b>GL-2765</b> <b>GL-2770</b>	 <p>Driver mounted remotely. (4) Cables &amp; (1) power cord per fixture.</p>	 <p>Driver mounted inside 12.5" canopy. (4) Cables and (1) power cords per fixture.</p>	 <p>Driver mounted remotely. (4) Canopies and (1) power feed canopy per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (1) Oversized canopy per fixture. (4) Canopies total. (1) Power feed point.</p>
<b>GL-2766</b> <b>GL-2771</b> <b>GL-2775</b> <b>GL-2780</b>	 <p>(1) Drivers mounted remotely. (4) Cables and (1) power cord per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (4) Cables and (1) power cords per fixture.</p>	 <p>Driver mounted remotely. (4) Canopies and (1) power feed canopy per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (1) Oversized canopy per fixture. (4) Canopies total. (1) Power feed point.</p>
<b>GL-2767</b> <b>GL-2772</b> <b>GL-2776</b> <b>GL-2781</b>	 <p>Drivers mounted remotely. (4) Cables &amp; (2) power cord per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (4) Cables and (2) power cords per fixture.</p>	 <p>Driver mounted remotely. (4) Canopies and (2) power feed canopy per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (2) Oversized canopy per fixture. (4) Canopies total. (2) Power feed points.</p>
<b>GL-2768</b> <b>GL-2773</b>	 <p>(2) Drivers mounted remotely. (4) Cables and (2) power cords per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (4) Cables and (2) power cords per fixture.</p>	 <p>Driver mounted remotely. (4) Canopies and (2) power feed canopy per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (2) Oversized canopies per fixture. (4) Canopies total. (2) Power feed points.</p>
<b>GL-2769</b> <b>GL-2774</b>	 <p>Drivers mounted remotely. (4) Cables and (2) power cords per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (4) Cables and (2) power cords per fixture.</p>	 <p>Driver mounted remotely. (4) Canopies and (2) power feed canopy per fixture.</p>	 <p>Drivers mounted inside 12.5" canopy. (2) Oversized canopies per fixture. (4) Canopies total. (2) Power feed points.</p>