

HELIO TUNABLE WHITE

Outer Acrylic Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Tunable White: LED option (TW) features tunable white technology that adjusts from 6500K-2700K.


LED Tuning: CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

LED Dimming: Intensity adjustable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

Acrylic: Satin white seamless outer acrylic is UL-94 HB Flame Class rated.

Cable Hanger: Comes with 72" cable and cord for on-site adjustability. Canopy painted textured white.

Finish: Highly durable oven cured no VOC premium powder coat.



SAMPLE CATALOG NUMBER:			
GL-2651-	TW6-	1-	A
MODEL NO.	LAMPING	HANGER	OPTIONS
GL-2650 W in 26" mm 660 20lbs B in 8 1/2" mm 215 9kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	TW4	1. Cable - Standard 	A. No Options LC. 150" Cord & Cable Supplied with 150" Cord & Cable. EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code.
GL-2651 W in 37 1/2" mm 950 30lbs B in 8 1/2" mm 215 13.5kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	TW6	2. Vertical Cable 	
GL-2652 W in 52" mm 1320 40lbs B in 8 1/2" mm 215 18kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	TW10	3. Vertical Cable 	

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW4	56W	3837	2700-6500
TW6	85W	6374	2700-6500
TW10	141W	10840	2700-6500