

ADAGIO

Indoor Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Body: GL-2000-2003 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2002-		L95-		S-	NSN-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT		
GL-2000 14lbs B in 18" mm 457 6 kg W in 23 1/4" mm 686 D in 7 5/8" mm 229 H in 29" mm 737	IN3. 3MED F4. 4CF L50. 5LED30 L55. 5LED35 L54. 5LED40	Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze	1. Stem 2. Cable 3. Arms 4. Stem Cluster	A. No Options F. Add Finial B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. W. White Opal Top Lens CF and INC only C. Clear Top Lens CF and INC only P. Perforated Top Lens CF and INC only	Standard overall height shown by model no. For custom overall height, specify in inches.		
GL-2001 21lbs B in 24" mm 610 10 kg W in 30 5/8" mm 780 D in 9" mm 230 H in 34" mm 865	IN3. 3MED F4. 4CF L60. 6LED30 L65. 6LED35 L64. 6LED40	Acrylic is UL-94 HB Flame Class rated.	Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SA-Satin Aluminum SB-Satin Brass PB-Polished Brass ORB-Oil Rubbed Bronze PC-Polished Copper SA-Satin Aluminum SC-Satin Chrome SN-Satin Nickel	Custom lengths available. For heights longer than standard, additional length will be added to top stem.	Multi-circuiting available upon request.			
GL-2002 29lbs B in 30" mm 762 13kg W in 36 1/4" mm 1016 D in 9 7/8" mm 270 H in 38" mm 965	IN6. 6MED F4. 4CF L90. 9LED30 L95. 9LED35 L94. 9LED40							
GL-2003 37lbs B in 38" mm 965 17kg W in 44 7/8" mm 1194 D in 11 5/8" mm 311 H in 42" mm 1067	IN6. 6MED F6. 6CF L120. 12LED30 L125. 12LED35 L124. 12LED40							
38" available in Satin Aluminum and powder coat finish only								

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Light Source Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens ¹	Total Wattage	Total Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L60	87	10544
IN3, IN6	Med	A-19	Medium		L65	87	10544
					L64	87	10544
					L90	130	16400
					L95	130	16400
					L94	130	16400
					L120	177	21794
					L125	177	21794
					L124	177	21794

¹Per MAXLITE & GE lamp products catalog
Contact factory for availability of other lamp configurations including induction and metal halide.

Universal Voltage unless otherwise specified.

