

APOLLO

Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable. Universal voltage.

LED Dimming: Standard 1% 0-10V dimming with LED lamping option.


Body: GL-2010-2013 rings spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

Canopy: Low profile. May be mounted on flat or sloped ceilings up to 40°.

Acrylic: Seamless acrylic is UL-94 HB Flame Class rated.







Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:								
GL-2012-		L95-		S-	NSN-	1-	A-	038
MODEL NO.	LAMPING		ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT	
GL-2010 14lbs B in 18" mm 460 6 kg W in 22" mm 560 D in 6 7/8" mm 175 H in 29" mm 740	IN3. 3MED F4. 4CF	L50. 5LED30 L55. 5LED35 L54. 5LED40	Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze	1. Stem  2. Cable  3. Arms  4. Stem Cluster  <small>Custom lengths available. For heights longer than standard, additional length will be added to top stem.</small>	A. No Options  F. Add Finial  B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. W. White Opal Top Lens CF and INC only C. Clear Top Lens CF and INC only P. Perforated Top Lens CF and INC only Multi-circuiting available upon request.	Standard overall height shown by model no. For custom overall height, specify in inches.	
								GL-2011 21lbs B in 24" mm 610 10 kg W in 28 1/4" mm 720 D in 7 7/8" mm 200 H in 34" mm 865
GL-2012 29lbs B in 30" mm 760 13kg W in 35" mm 890 D in 8 7/8" mm 225 H in 38" mm 965	IN6. 6MED F4. 4CF	L90. 9LED30 L95. 9LED35 L94. 9LED40	38" available in Satin Aluminum and powder coat finish only					
GL-2013 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 10 3/8" mm 265 H in 42" mm 1070	IN6. 6MED F6. 6CF	L120. 12LED30 L125. 12LED35 L124. 12LED40						

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens ¹	Code	Total Wattage	Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3 4PIN	1530/2040/2690	L90	130	3000	16400
IN3, IN6	Med	A-19	Medium		L95	130	3500	16400
	Total	Delivered			L94	130	4000	16400
Code	Wattage	Kelvin	Lumens		L120	177	3000	21794
L50	71	3000	8971		L125	177	3500	21794
L55	71	3500	8971		L124	177	4000	21794
L54	71	4000	8971					
L60	87	3000	10544					
L65	87	3500	10544					
L64	87	4000	10544					

¹Per MAXLITE & GE lamp products catalog
Contact factory for availability of other lamp configurations including induction and metal halide.