

CYLINDER - QUICKSHIP

Outdoor ADA Wall Sconce



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency high-power LED. Lumen maintenance +90% over 50,000 hour life. Light source is field replaceable.


Driver: Standard 1% 0-10V dimming. Max remote driver installation distance: 25ft from fixture body. Universal voltage 120-277V.

Body: Cast aluminum.

Mounting: -Driver mounted in 4" square by 2 1/8" deep junction box:
Steel City #52171 or equivalent (supplied by others)

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-6540-				
	B-	R2-R2	TBL-	A
MODEL NO.	LAMPING	REFLECTOR	FINISH	OPTIONS
GL-6540 W 5" in H 9 1/4" in E 4" in	B. LED35	Up R2. 20° Fresnel Lens R3. 30° Flat, Clear Lens Down R2. 20° Fresnel Lens R3. 30° Flat, Clear Lens	Textured: TBL - Black TBZ - Bronze	A. No Options
GL-6541 W 5" in H 6" in E 4" in	B. LED35	Up R5. 50° Flat, Clear Lens CC. Closed Cap Down R5. 50° Flat, Clear Lens CC. Closed Cap		
GL-6542 W 5" in H 7 5/8" in E 4" in	B. LED35	Up R2. 20° Fresnel Lens R3. 30° Flat, Clear Lens Down R5. 50° Flat, Clear Lens CC. Closed Cap		
GL-6543 W 5" in H 7 5/8" in E 4" in	B. LED35	Up R5. 50° Flat, Clear Lens CC. Closed Cap Down R2. 20° Fresnel Lens R3. 30° Flat, Clear Lens		

* All dimensions are nominal.

Light Source Definition

— Specifications per side —						
Code	Kelvin	Reflector	CRI	Total Wattage	Rated Life Hrs	Delivered Lumens
LED35	3500K	20°	+80	14W	50000	1462*
		30°	+80	14W	50000	1030
		50°	+80	14W	50000	1284

Fixture is ETL listed for wet locations
Complete LM-79 data available at glighting.com