

ESSEX

Indoor Pendant






9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@lighting.com www.glighting.com

GENERAL SPECIFICATION

- Body:** GL-2050-2053 ring spun in 18ga steel or .050 aluminum.
- Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
GL-2050 14lbs B in 18" mm 460 6 kg D in 8 3/4" mm 220 H in 29" mm 735	IN3. 3MED F4. 4CF	Standard: S. Satin White Optional: W. White Opal F. Faux Alabaster M. Earth Marble	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBN-Terra Brown TBZ-Textured Bronze Premium: SA-Satin Aluminum SB-Satin Brass PB-Polished Brass ORB-Oil Rubbed Bronze PC-Polished Copper SA-Satin Aluminum SC-Satin Chrome SN-Satin Nickel	1. Stem  4. Stem Cluster 	A. No Options B. Damp Location Available in powder coat or Satin Aluminum finish. DE. ECO Dimming Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. DV. Mark VII Dimming Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. DX. Mark X Dimming Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. E. Emergency Ballast Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°-131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. Multi-circuiting available upon request.	Standard overall height shown by model no. For custom overall height, specify in inches.
GL-2051 21lbs B in 24" mm 610 10 kg D in 10" mm 255 H in 34" mm 865	IN3. 3MED F4. 4CF	Acrylic is UL-94 HB Flame Class rated.		Custom lengths available. For heights longer than standard, additional length will be added to top stem.		
GL-2052 29lbs B in 30" mm 760 13kg D in 11" mm 280 H in 38" mm 965	IN6. 6MED F4. 4CF					
GL-2053 37lbs B in 38" mm 965 17kg D in 12 1/2" mm 320 H in 42" mm 1070	IN6. 6MED F6. 6CF					

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens ¹
F4, F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690
IN3, IN6	Med	A-19	Medium	

¹Per MAXLTE & GE lamp products catalog
Contact factory for availability of other lamp configurations including induction and metal halide.

Universal Voltage unless otherwise specified.