

# HELIO TUNABLE WHITE

## Outer Acrylic Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Tunable White:** LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

**LED Tuning:** CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**LED Dimming:** Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.


**Acrylic:** Satin white seamless outer acrylic is UL-94 HB Flame Class rated.

**Cable Hanger:** Comes with 72" cable and white cord for on-site adjustability.

**Canopy:** Painted textured white.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:			
GL-2651-	TW6-	1-	A
MODEL NO.	LAMPING	HANGER	OPTIONS
<b>GL-2650</b> W in 26" mm 660 20lbs B in 8 1/2" mm 215 9kg H in 20"-68" mm 510-1730  Fixture Painted Textured White	<b>TW4</b>	<b>1. Cable - Standard</b> 	<b>A. No Options</b> <b>LC. 150" Cord &amp; Cable</b> Supplied with 150" Cord & Cable. <b>EL. Emergency Ballast</b> Integrally operates two LED strips. Integral test switch. Specify voltage after code.
<b>GL-2651</b> W in 37 1/2" mm 950 30lbs B in 8 1/2" mm 215 13.5kg H in 20"-68" mm 510-1730  Fixture Painted Textured White	<b>TW6</b>	<b>2. Vertical Cable</b> 	
<b>GL-2652</b> W in 52" mm 1320 40lbs B in 8 1/2" mm 215 18kg H in 20"-68" mm 510-1730  Fixture Painted Textured White	<b>TW10</b>	<b>3. Vertical Cable</b> 	

All Dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW4	56W	3837	2700-6500
TW6	85W	6374	2700-6500
TW10	141W	10840	2700-6500

Universal Voltage unless otherwise specified.