

HELIO WARM DIM

Outer Acrylic Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 0-10V dimming.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.




Cable Hanger: Comes with 72" cable and white cord for on-site adjustability.

Canopy: Painted textured white.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:			
GL-2651-	WD6-	1-	A
MODEL NO.	LAMPING	HANGER	OPTIONS
GL-2650 W in 26" mm 660 20lbs B in 8 1/2" mm 215 9kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	WD4	1. Cable - Standard 	A. No Options LC. 150" Cord & Cable Supplied with 150" Cord & Cable. EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code.
GL-2651 W in 37 1/2" mm 950 30lbs B in 8 1/2" mm 215 13.5kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	WD6	2. Vertical Cable 	
GL-2652 W in 52" mm 1320 40lbs B in 8 1/2" mm 215 18kg H in 20"-68" mm 510-1730 Fixture Painted Textured White	WD10	3. Vertical Cable  GL-2650 & GL-2651 (3) Canopies total. GL-2652 (4) Canopies total.	

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
WD4	82W	3837	3500-1800
WD6	124W	6374	3500-1800
WD10	206W	10840	3500-1800

Universal Voltage unless otherwise specified.