

# MARINER

## Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** GL-2180-2183 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:							
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT	
<b>GL-2180</b> 14lbs B in 18" mm 460 6 kg W in 22" mm 560 D in 7 5/8" mm 195 H in 29" mm 735	<b>IN3. 3MED</b> <b>F4. 4CF</b>	<b>L50. 5LED30</b> <b>L55. 5LED35</b> <b>L54. 5LED40</b>	<b>Standard:</b> <b>S. Satin White</b>  <b>Optional:</b> <b>W. White Opal</b> <b>F. Faux Alabaster</b> <b>M. Earth Marble</b>	<b>Standard:</b> <b>Powder Coat</b> <b>BLK-Black</b> <b>BL-Blue</b> <b>GR-Gray</b> <b>LG-Light Gray</b> <b>BE-Beige</b> <b>PAB-Antique Brass</b> <b>PA-Painted Aluminum</b> <b>PTC-Painted Copper</b> <b>WH-White</b> <b>DBZ-Dark Bronze</b> <b>NSN-New Satin Nickel</b> <b>BRN-Brown</b> <b>RD-Red</b> <b>CH-Champagne</b> <b>RG-Reed Green</b> <b>SG-Sungold</b> <b>GM-Gun Metal</b> <b>POR-Oil Rubbed Bronze</b>  <b>Textured Powder</b> <b>TLV-Light Verdigris</b> <b>TWH-Textured White</b> <b>TBL-Textured Black</b> <b>TS-Textured Silver</b> <b>TBN-Terra Brown</b> <b>TBZ-Textured Bronze</b>  <b>Premium:</b> <b>SA-Satin Aluminum</b> <b>SB-Satin Brass</b> <b>PB-Polished Brass</b> <b>ORB-Oil Rubbed Bronze</b> <b>PC-Polished Copper</b> <b>SA-Satin Aluminum</b> <b>SC-Satin Chrome</b> <b>SN-Satin Nickel</b>	<b>1. Stem</b>  <b>2. Cable</b>  <b>3. Arms</b>  <b>4. Stem Cluster</b>  <small>Custom lengths available. For heights longer than standard, additional length will be added to top stem.</small>	<b>A. No Options</b> <b>F. Add Finial</b>  <b>B. Damp Location</b> Available in powder coat or Satin Aluminum finish. <b>DE. ECO Dimming</b> Lutron Ecosystem dimming CF lamping option. Specify voltage and wattage after dimming code. <b>DV. Mark VII Dimming</b> Advance Mark VII dimming CF lamping option. Specify voltage and wattage after dimming code. <b>DX. Mark X Dimming</b> Advance Mark X dimming CF lamping option. Specify voltage and wattage after dimming code. <b>E. Emergency Ballast</b> Operates one fluorescent lamp. Remote mount up to 5' from lamps in controlled environment with an area temperature range of 32°- 131°F. Non-dimming compact fluorescent only. Specify 120 or 277 voltage. <b>EL. Emergency LED</b> Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. <b>W. White Opal Top Lens</b> CF and INC only <b>C. Clear Top Lens</b> CF and INC only <b>P. Perforated Top Lens</b> CF and INC only  Multi-circuiting available upon request.	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2181</b> 21lbs B in 24" mm 610 10 kg W in 28 1/4" mm 720 D in 8 5/8" mm 220 H in 34" mm 865	<b>IN3. 3MED</b> <b>F4. 4CF</b>	<b>L60. 6LED30</b> <b>L65. 6LED35</b> <b>L64. 6LED40</b>	Acrylic is UL-94 HB Flame Class rated.				
<b>GL-2182</b> 29lbs B in 30" mm 760 13kg W in 35" mm 890 D in 9 5/8" mm 245 H in 38" mm 965	<b>IN6. 6MED</b> <b>F4. 4CF</b>	<b>L90. 9LED30</b> <b>L95. 9LED35</b> <b>L94. 9LED40</b>					
<b>GL-2183</b> 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 11 1/8" mm 285 H in 42" mm 1070	<b>IN6. 6MED</b> <b>F6. 6CF</b>	<b>L120. 12LED30</b> <b>L125. 12LED35</b> <b>L124. 12LED40</b>	38" available in Satin Aluminum and powder coat finish only				

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Fluorescent	Lamp Base	Lamp Lumens <sup>1</sup>	Code	Total Wattage	Kelvin	Delivered Lumens
F4, F6	CF	CF 26W/32W/42W	GX24q-3/4 4PIN	1530/2040/2690	L60	87	3000	10544
IN3, IN6	Med	A-19	Medium		L65	87	3500	10544
					L64	87	4000	10544
					L90	130	3000	16400
					L95	130	3500	16400
					L94	130	4000	16400
					L120	177	3000	21794
					L125	177	3500	21794
					L124	177	4000	21794

<sup>1</sup>Per MAXLTE & GE lamp products catalog  
Contact factory for availability of other lamp configurations including induction and metal halide.

Universal Voltage unless otherwise specified.

