

TAHOE II TUNABLE WHITE

Interior Square Semi-Surface Mount



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Tunable White: LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

LED Tuning: CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.



LED Dimming: Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.

Shade: Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.

Standard textured white finish



SAMPLE CATALOG NUMBER: GL-3732-				TW5-	W-	A
MODEL NO.				LAMPING	SHADE	OPTIONS
GL-3732	W in 24"	mm 610	15lbs 7kg	TW5	W White C Cream R Red BL Blue O Olive S Stone	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
GL-3733	W in 30"	mm 760	18lbs 8kg	TW5		
GL-3734	W in 36"	mm 915	20lbs 9kg	TW8	Washable: WW White WC Cream WT Tan WB Brown	
GL-3735	W in 48"	mm 1220	25lbs 11.5kg	TW8		

All Dimensions are nominal.

Shade

Standard

White Cream Blue Stone Red Olive

Washable - Trilam

White Tan Cream Brown

Custom fabrics available upon request. Contact factory.
Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW5	72	7736	3500-1800
TW8	114	12248	3500-1800

Universal Voltage unless otherwise specified.