

# CONE

## Interior Surface Mount




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish available in white, black, and gold liquid paint.
- Non-white inner finishes will reduce lumen output.
- Surge Protection:** External surge protector provided as standard.



### SAMPLE CATALOG NUMBER:

GL-3350-

MODEL NO.	E-	BLK-	MO-	A
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
<b>GL-3350</b> 8lbs W in 16" 3.6kg H in 11"	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue  Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone  <b>Premium:</b> SA-Satin Aluminum	<b>Standard:</b> MO-Matches Outer Finish Liquid Paint WH-White BLK-Black GL-Gold	<b>A. No Options</b> <b>DM. DMX Dimming</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. <b>EL. Emergency LED</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-3351</b> 10lbs W in 24" 4.5kg H in 15 3/8"	G. 1LED30 H. 1LED35 I. 1LED40 J. 1LED30 K. 1LED35 L. 1LED40 M. 1LED30 N. 1LED35 O. 1LED40 V. 1LED30* W. 1LED35* X. 1LED40*	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.

All Dimensions are nominal.

### Light Source Definition

Downlight Output						Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	17W	1534	3000	80	V	1LED30	68W	5076*	3000	80
B	1LED35	17W	1534	3500	80	W	1LED35	68W	5076*	3500	80
C	1LED40	17W	1534	4000	80	X	1LED40	68W	5076*	4000	80
D	1LED30	24W	2148	3000	80						
E	1LED35	24W	2148	3500	80						
F	1LED40	24W	2148	4000	80						
G	1LED30	15W	1361	3000	80						
H	1LED35	15W	1361	3500	80						
I	1LED40	15W	1361	4000	80						
J	1LED30	26W	2334	3000	80						
K	1LED35	26W	2334	3500	80						
L	1LED40	26W	2334	4000	80						
M	1LED30	39W	3501	3000	80						
N	1LED35	39W	3501	3500	80						
O	1LED40	39W	3501	4000	80						

Universal Voltage unless otherwise specified.

Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

