

CUBIX II

Outer Acrylic Interior Pendant








9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.
Lower Output: Lamping code ending with LO features lower lumen output.
LED Dimming: Standard 1% 0-10V dimming.
Driver: Max remote driver installation distance:
 White LED 25ft from fixture body and RGB 45ft from fixture body.
 See Cubix/Apex Hanger Guide for more information.
RGB: DMX controller supplied by others.
Cable Hanger: Standard 150" cable and white cord for on-site adjustability.
Canopy: Matches fixture finish.
Finish: Highly durable oven cured no VOC premium powder coat.
Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:		GL-2772-	J-	BLK-	1-	A
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS		
GL-2770 W in 24"x24" 10lbs B in 3" 4.5kg H in 11"-145"	A. 24LED30 AL. 24LED30LO B. 24LED35 BL. 24LED35LO C. 24LED40 CL. 24LED40LO D. RGB	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue	1. Cable - Standard  Drivers mounted remotely. See Cubix Hanger Guide for more information. 2. Oversized  Drivers mounted inside oversized canopy. See Cubix Hanger Guide for more information.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.		
GL-2771 W in 36"x36" 15lbs B in 3" 6.8kg H in 18.75"-145"	E. 36LED30 EL. 36LED30LO F. 36LED35 FL. 36LED35LO G. 36LED40 GL. 36LED40LO H. RGB	Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone Premium: SA- Satin Aluminum	3. Vertical Remote Canopy  Drivers mounted remotely. See Cubix Hanger Guide for more information.			
GL-2772 W in 48"x48" 15lbs B in 3" 6.8kg H in 18.75"-145"	I. 48LED30 IL. 48LED30LO J. 48LED35 JL. 48LED35LO K. 48LED40 KL. 48LED40LO L. RGB		4. Vertical Integral Canopy  Drivers mounted inside 12.5" oversized canopy. See Cubix Hanger Guide for more information. Hanger options 1&3 supplied with remote driver box.			
GL-2773 W in 60"x60" 19lbs B in 3" 10kg H in 25.5"-142"	M. 60LED30 ML. 60LED30LO N. 60LED35 NL. 60LED35LO O. 60LED40 OL. 60LED40LO P. RGB					
GL-2774 W in 72"x72" 22lbs B in 3" 10kg H in 25.5"-142"	Q. 72LED30 QL. 72LED30LO R. 72LED35 RL. 72LED35LO S. 72LED40 SL. 72LED40LO T. RGB					

All Dimensions are nominal.

Light Source Definition

High Lumen Output						Low Lumen Output					
Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
24LED30/35/40	78	+85	50000	6803	3000/3500/4000	24LED30/35/40LO	43	+85	50000	3605*	3000/3500/4000
36LED30/35/40	112	+85	50000	10203*	3000/3500/4000	36LED30/35/40LO	56	+85	50000	5102*	3000/3500/4000
48LED30/35/40	157	+85	50000	14682	3000/3500/4000	48LED30/35/40LO	85	+85	50000	7210*	3000/3500/4000
60LED30/35/40	193	+85	50000	18006	3000/3500/4000	60LED30/35/40LO	112	+85	50000	9523*	3000/3500/4000
72LED30/35/40	216	+85	50000	18503	3000/3500/4000	72LED30/35/40LO	134	+85	50000	10203*	3000/3500/4000

RGB Contact Factory for Details

Universal Voltage unless otherwise specified.

*Pending IES Testing