

CUBIX - Acoustic

Inner Acrylic Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- Acoustic Panel:** 1/2" center acoustic panel reduces noise level in environment.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming.
- Cable Hanger:** Standard 150" cable and white cord for on-site adjustability. Canopy painted textured white.
- Canopy:** Max remote driver installation distance: White LED 25ft from fixture body and RGB 45ft from fixture body. See Cubix Hanger Guide for more information.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- RGB:** DMX controller supplied by others.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2826-		F-	BLK-	ABLK-	1-	A
MODEL NO.	LAMPING		FINISH	ACOUSTIC	HANGER	OPTIONS
GL-2825 10lbs W in 24"x24" 4.5kg B in 3" H in 11"-145"	A. 24LED30 B. 24LED35 C. 24LED40 D. RGB	AL. 24LED30LO BL. 24LED35LO CL. 24LED40LO	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue	Standard: Acoustic ABLK- Black ABL- Blue AGR- Gray ALG- Light Gray ARD- Red	1. Cable - Standard Drivers mounted remotely. See Cubix Hanger Guide for more information. 2. Oversized Drivers mounted inside oversized canopy. See Cubix Hanger Guide for more information. 3. Vertical Remote Canopy Drivers mounted remotely. See Cubix Hanger Guide for more information. 4. Vertical Integral Canopy Drivers mounted inside 12.5" oversized canopy. See Cubix Hanger Guide for more information. Hanger options 1&3 supplied with remote driver box.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
GL-2826 15lbs W in 36"x36" 6.8kg B in 3" H in 18.75"-145"	E. 36LED30 F. 36LED35 G. 36LED40 H. RGB	EL. 36LED30LO FL. 36LED35LO GL. 36LED40LO				
GL-2827 15lbs W in 48"x48" 6.8kg B in 3" H in 18.75"-145"	I. 48LED30 J. 48LED35 K. 48LED40 L. RGB	IL. 48LED30LO JL. 48LED35LO KL. 48LED40LO				
GL-2828 19lbs W in 60"x60" 10kg B in 3" H in 25.5"-142"	M. 60LED30 N. 60LED35 O. 60LED40 P. RGB	ML. 60LED30LO NL. 60LED35LO OL. 60LED40LO	Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone			
GL-2829 22lbs W in 72"x72" 10kg B in 3" H in 25.5"-142"	Q. 72LED30 R. 72LED35 S. 72LED40 T. RGB	QL. 72LED30LO RL. 72LED35LO SL. 72LED40LO	Premium: SA- Satin Aluminum			

All Dimensions are nominal.

Light Source Definition

High Lumen Output						Low Lumen Output					
Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
24LED30/35/40	77	+85	50000	6048	3000/3500/4000	24LED30/35/40LO	43	+85	50000	3207*	3000/3500/4000
36LED30/35/40	110	+85	50000	9439	3000/3500/4000	36LED30/35/40LO	56	+85	50000	4536*	3000/3500/4000
48LED30/35/40	156	+85	50000	13932	3000/3500/4000	48LED30/35/40LO	85	+85	50000	6410*	3000/3500/4000
60LED30/35/40	200	+85	50000	15119*	3000/3500/4000	60LED30/35/40LO	112	+85	50000	8466*	3000/3500/4000
72LED30/35/40	215	+85	50000	16956	3000/3500/4000	72LED30/35/40LO	134	+85	50000	9071*	3000/3500/4000

RGB Contact Factory for Details

Universal Voltage unless otherwise specified.

*Pending IES Testing