

MARINA II RGB+WHITE

Interior Round Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

RGB+White: LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source.

A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped

ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

RGB: LED option features RGB color changing light source. RGB channel wired DMX ready.

Static Color: LED options (Red, Green, or Blue) feature static color.


Shade: Standard white fabric shade with integral satin white diffuser.



Custom shapes, sizes, and colors available.

Finish: Highly durable oven cured no VOC premium powder coat.

DMX: Controls by others.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:							
GL-2742-	HH-	W-	NSN-	5-	A-	072	
MODEL NO.	LAMPING		SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-2742 W in 24" 15lbs D in 11.5" 7kg H Specify	DD. RED EE. GREEN FF. BLUE GG. RGB*	HH. RGB30* II. RGB35* JJ. RGB40*	W White C Cream R Red BL Blue O Olive S Stone	Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5. Two power cords with all RGB and RGB+W lamping codes.	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.
GL-2743 W in 30" 18lbs D in 12.5" 8kg H Specify	KK. RED LL. GREEN MM. BLUE NN. RGB*	OO. RGB30* PP. RGB35* QQ. RGB40*	WW White WC Cream WT Tan WB Brown	Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone			
GL-2744 W in 36" 20lbs D in 13.5" 9kg H Specify	RR. RED SS. GREEN TT. BLUE UU. RGB*	VV. RGB30* WW. RGB35* XX. RGB40*					
GL-2745 W in 48" 25lbs D in 15.5" 11.5kg H Specify	YY. RED ZZ. GREEN AB. BLUE AC. RGB*	AD. RGB30* AE. RGB35* AF. RGB40*					

All Dimensions are nominal.
*DMX controls supplied by others.

Shade

Standard						
 White	 Cream	 Blue	 Stone	 Red	 Olive	
Washable - Trilam						
 White	 Tan	 Cream	 Brown			

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Fixture	Total Wattage	Rated CRI	Rated Life Hrs	Delivered Lumens
GL-2742	72	+80	50000	7436
GL-2743	72	+80	50000	7436
GL-2744	114	+80	50000	12248
GL-2745	114	+80	50000	12248

Universal Voltage unless otherwise specified.