

# MEDI

## Interior Surface Mount



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs.

**LED Dimming:** Standard 1% 0-10V dimming.

**Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.


**Acrylic:** Acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Inner Finish:** Inner finish available in white, black, and gold liquid paint.

Non-white inner finishes will reduce lumen output.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3356-				
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
<b>GL-3355</b> 8lbs Win 16" 3.6kg H in 7 3/8"	<b>A.</b> 1LED30 <b>B.</b> 1LED35 <b>C.</b> 1LED40 <b>D.</b> 1LED30 <b>E.</b> 1LED35 <b>F.</b> 1LED40 <b>G.</b> 1LED30 <b>H.</b> 1LED35 <b>I.</b> 1LED40 <b>V.</b> 1LED30* <b>W.</b> 1LED35* <b>X.</b> 1LED40*	<b>Standard:</b> Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Stone  <b>Premium:</b> <b>SA</b> -Satin Aluminum	<b>Standard:</b> <b>MO</b> -Matches Outer Finish Liquid Paint <b>WH</b> -White <b>BLK</b> -Black <b>GL</b> -Gold	<b>A.</b> No Options <b>DM.</b> DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-3356</b> 10lbs Win 24" 4.5kg H in 11 9/16"				
<b>GL-3357</b> 15lbs Win 32" 6.8kg H in 15 11/16"				
	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.	

All Dimensions are nominal.

### Light Source Definition

Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	15W	1538	3000	80
B	1LED35	15W	1538	3500	80
C	1LED40	15W	1538	4000	80
D	1LED30	26W	2637	3000	80
E	1LED35	26W	2637	3500	80
F	1LED40	26W	2637	4000	80
G	1LED30	39W	3956	3000	80
H	1LED35	39W	3956	3500	80
I	1LED40	39W	3956	4000	80
V	1LED30	68W	6009*	3000	80
W	1LED35	68W	6009*	3500	80
X	1LED40	68W	6009*	4000	80

\*Projected

Universal Voltage unless otherwise specified.  
 Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.