

OCULUS

Interior Pendant



9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

LED: High efficiency mid-power LEDs are field serviceable.

LED Dimming: Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless acrylic is UL-94 HB Flame Class rated.


Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat. Spinning interior painted textured white.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2641-		E-	PTC-	1-	A
MODEL NO.		LAMPING	FINISH	HANGER	OPTIONS
GL-2640	W 26" in 660 mm 10lbs B 7 1/2" in 190 mm 4.5kg H 20"-68" in 510-1730 mm	A. 4LED30 B. 4LED35 C. 4LED40	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone Premium: SA -Satin Aluminum Not available in standard white finish	1. Cable 	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32"-131°F. Specify 120 or 277 voltage.
GL-2641	W 37" in 940 mm 15lbs B 7 1/2" in 190 mm 6.8kg H 20"-68" in 510-1730 mm	D. 5LED30 E. 5LED35 F. 5LED40			

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	Rated CRI	Rated Life Hrs	Delivered Lumens	Kelvin
4LED30	57W	+80	50000	4310	3000
4LED35	57W	+80	50000	4310	3500
4LED40	57W	+80	50000	4310	4000
5LED30	72W	+80	50000	5320	3000
5LED35	72W	+80	50000	5320	3500
5LED40	72W	+80	50000	5320	4000

Universal Voltage unless otherwise specified.