

ORBIS - Acoustic

Inner Acrylic Interior Surface Mount





9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- Acoustic Panel:** 1/2" center acoustic panel reduces noise level in environment.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Max remote driver installation distance: White LED 25ft from fixture body and RGB 45ft from fixture body. See Orbis Hanger Guide for more information.
- RGB:** DMX controller supplied by others.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Mounting Plate:** Matches fixture finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-3792-		F-	BLK-	ABLK-	A
MODEL NO.	LAMPING	FINISH	ACOUSTIC	OPTIONS	
GL-3790 W 24" 10lbs B 3" 4.5kg H 3.5"	A. 24LED30 B. 24LED35 C. 24LED40 D. RGB	AL. 24LED30LO BL. 24LED35LO CL. 24LED40LO	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone Premium: SA-Satin Aluminum*	Standard: Acoustic ABLK-Black ABL-Blue AGR-Gray ALG-Light Gray ARD-Red	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-3791 W 36" 15lbs B 3" 6.8kg H 3.5"	U. 36LED30 V. 36LED35 W. 36LED40 X. RGB	UL. 36LED30LO VL. 36LED35LO WL. 36LED40LO			
GL-3792 W 48" 15lbs B 3" 6.8kg H 3.5"	E. 48LED30 F. 48LED35 G. 48LED40 H. RGB	EL. 48LED30LO FL. 48LED35LO GL. 48LED40LO			
GL-3793 W 60" 18lbs B 3" 8.2kg H 3.5"	Y. 60LED30 Z. 60LED35 AA. 60LED40 BB. RGB	YL. 60LED30LO ZL. 60LED35LO AAL. 60LED40LO			
GL-3794 W 72" 22lbs B 3" 10kg H 3.5" Fixture Built with Four Acrylic Segments	I. 72LED30 J. 72LED35 K. 72LED40 L. RGB	IL. 72LED30LO JL. 72LED35LO KL. 72LED40LO			

All Dimensions are nominal.

Light Source Definition

High Lumen Output						Low Lumen Output					
Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens*	Kelvin
24LED30/35/40	54	+80	50000	4135	3000/3500/4000	24LED30LO/35LO/40LO	32	+80	50000	2481	3000/3500/4000
36LED30/35/40	76	+80	50000	7261	3000/3500/4000	36LED30LO/35LO/40LO	46	+80	50000	4357	3000/3500/4000
48LED30/35/40	106	+80	50000	10096	3000/3500/4000	48LED30LO/35LO/40LO	64	+80	50000	6058	3000/3500/4000
60LED30/35/40	131	+80	50000	12991	3000/3500/4000	60LED30LO/35LO/40LO	73	+80	50000	7143	3000/3500/4000
72LED30/35/40	152	+80	50000	14838	3000/3500/4000	72LED30LO/35LO/40LO	104	+80	50000	10159	3000/3500/4000
RGB	Contact Factory for Details										

Universal Voltage unless otherwise specified. *Estimate