

# ROCKFORD

## Indoor Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Down Light:** 90CRI 17 watt 2000 lumen module. Lamping code ending with "DL" includes downlight.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.
- Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2425-	A-	W-	NSN-	1-	A-	34
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
<b>GL-2425</b> 12lbs W in 11 1/8" mm 280 6 kg B in 26" mm 635 H in 34" mm 890  Fixture does not include downlight	<b>U.</b> 4LED30 <b>V.</b> 4LED35 <b>W.</b> 4LED40 <b>T.</b> RGB	<b>Standard:</b> <b>W.</b> White Opal <b>S.</b> Satin White  Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze  Textured Powder <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBZ-</b> Textured Bronze <b>TST-</b> Stone  <b>Premium:</b> <b>SA-</b> Satin Aluminum	<b>1. Stem</b>  Remote driver.  <b>2. Cable</b>  Standard white power cord. Remote driver.  <b>3. Oversized with Stem</b>  12" Canopy  <b>4. Oversized with Cable</b>  Standard white power cord. 12" Canopy.	<b>A.</b> No Options <b>BC.</b> Black Cord Fixture supplied with black power cord. <b>LC.</b> 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. <b>EL.</b> Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2426</b> 21lbs W in 11 1/8" mm 280 10 kg B in 33 3/8" mm 850 H in 44" mm 1120  Fixture includes downlight	<b>AA.</b> 4LED30DL <b>BB.</b> 4LED35DL <b>CC.</b> 4LED40DL <b>T.</b> RGB				<b>Hanger options 1&amp;2 supplied with remote driver box.</b>	

All dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin	Code	*Total Wattage	*Delivered Lumens	Kelvin
U	51W	5556	3000	AA	68W	7248	3000
V	51W	5556	3500	BB	68W	7248	3500
W	51W	5556	4000	CC	68W	7248	4000
RGB	Contact Factory for Details						

Universal Voltage unless otherwise specified. \*Includes downlight wattage (17W) and lumen output (1692lm)