

SELENE RGB+W

Inner Acrylic Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

RGB+White: LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 0-10V dimming standard.

RGB: LED option features RGB color changing light source. RGB channel wired DMX ready.

LED Dimming: Standard 0-10V dimming. TRIAC, DALI, or DMX available upon request.

Acrylic: Satin white seamless outer acrylic is UL-94 HB Flame Class rated.


Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat.

Body: Ring spun in 1/8" aluminum.

DMX: Controls by others.



SAMPLE CATALOG NUMBER:



GL-2581-

AA-

PTC-

1-

A-

MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS
GL-2580 W in 26" mm 660 20lbs B in 7 1/2" mm 190 9kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	O. RED P. GREEN Q. BLUE R. RGB* S. RGB30* T. RGB35* U. RGB40*	Standard: BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	1. Cable  2. Vertical Cable 	A. No Options EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code. Available GL-2581 only. BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.
GL-2581 W in 37" mm 940 30lbs B in 7 1/2" mm 190 13.5kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	V. RED W. GREEN X. BLUE Y. RGB* Z. RGB30* AA. RGB35* BB. RGB40*			

All Dimensions are nominal.

*DMX controls supplied by others.

Light Source Definition

Fixture	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens
GL-2580	85	+80	50000	3837
GL-2581	113	+80	50000	6374

Universal Voltage unless otherwise specified.