

SELENE WARM DIM

Inner Acrylic Interior Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Warm Dim: LED option (WD) features warm dimming technology that dims smoothly from 3500K-1800K with standard 0-10V dimming.

LED Dimming: Standard 0-10V dimming. TRIAC, DALI, or DMX available upon request.


Acrylic: Satin white seamless outer acrylic is UL-94 HB Flame Class rated.



Cable Hanger: Comes with 72" cable and cord for on-site adjustability.

Canopy: Matches fixture finish.

Finish: Highly durable oven cured no VOC premium powder coat.

Body: Ring spun in 1/8" aluminum.



SAMPLE CATALOG NUMBER: GL-2581-				
MODEL NO.	WD8-	PTC-	1-	A-
	LAMPING	FINISH	HANGER	OPTIONS
GL-2580 W in 26" mm 660 20lbs B in 7 1/2" mm 190 9kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	WD6	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	1. Cable  2. Vertical Cable 	A. No Options EL. Emergency Ballast Integrally operates two LED strips. Integral test switch. Specify voltage after code. Available GL-2581 only. BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.
GL-2581 W in 37" mm 940 30lbs B in 7 1/2" mm 190 13.5kg H in 20"-68" mm 510-1730 Fixture supplied with 72" of cord and cable. Adjust on-site. Minimum 20" OAH. Contact factory for OAH greater than 68".	WD8			

All Dimensions are nominal.

Light Source Definition

Code	Total Wattage	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
WD6	124	+80	50000	5362	3500-1800
WD8	165	+80	50000	6669	3500-1800

Universal Voltage unless otherwise specified.