## SKYLINE

## Interior Schoolhouse Sconce

9777 Reavis Park Drive St. Louis, MO 63123 800.331.2425 or 314.631.6000


## **GENERAL SPECIFICATION**


**LED:** High efficiency mid-power LEDs are field serviceable.

**LED Dimming:** 1% 0-10V dimming standard with LED lamping option.

**Body:** 18ga steel or .050 aluminum glass fitter. **Glass:** White opal diffuser hand blown in the USA.

**Finish:** Highly durable oven cured no VOC premium powder coat. **Surge Protection:** External surge protector provided as standard.







SAMPLE CATALOG NUMBER:				
GL-4315-	L5-	A-	SN-	A-
MODEL NO.	LAMPING	GLASS	FINISH	OPTION(S)
GL-4315	L0.11LED30 L5.11LED35 L4.11LED40	A. Skyline Glass	Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum  B.Da Avail Alumin EL. Rem source with a 32°-13	A. No Options  B. Damp Location Available in powder coat or Satin Aluminum finish.  EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
GL-4316	IN1.1MED 120 volt only			

All dimensions are nominal.

**Light Source Definition** 

			Rated	
<u>Code</u>	<u>LED</u>	<u>Kelvin</u>	Life Hrs	Lumens
11LED30	11W LED	3000	50000	1460
11LED35	11W LED	3500	50000	1460
11LED40	11W LED	4000	50000	1460

Universal Voltage unless otherwise specified.