

SONOMA II

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request.
- Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.
- Acrylic:** Satin white acrylic bottom diffuser is UL-94 HB Flame Class rated.
- Canopy:** Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.
- Cable Hanger Option:** Supplied with standard 72" white cord and cable. Field adjustable.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping or cluster options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2905-	L55-	W-	NSN-	1-	A-	045
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
GL-2905 W in 30 1/8" 15lbs B in 34" 7kg H in 45"	L50. 5LED30 L55. 5LED35 L54. 5LED40 IN4. 4MED*	Standard: W White C Cream R Red BL Blue O Olive S Stone Washable: WW White WC Cream WT Tan WB Brown	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone Premium: SA -Satin Aluminum	1. Stem Mount Drivers mounted integrally 2. Cable Mount Drivers mounted integrally	A. No Options BC. Black Cord Fixture supplied with black power cord. LC. 150" Cord & Cable Fixture supplied with 150" of cable and standard white cord or optional black cord. EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Standard 45" overall height. Available up to 93". For custom overall height, contact factory.


All Dimensions are nominal. 120V only*

Shade

Standard with Integral White Satin Bottom Diffuser



Washable Trilam with Integral White Satin Bottom Diffuser



Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Code	Total Wattage	Source Lumens	Kelvin	Code	Lamp	Lamp Base
L50	72W	9750	3000	IN4	A-19	Medium
L55	72W	9750	3500			
L54	72W	9750	4000			

Universal Voltage unless otherwise specified.