Indoor ADA Sconce

9777 Reavis Park Drive St. Louis, MO 63123 800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

Body: Formed .050 aluminum body with 1/4" x 1/2" aluminum rails and 1/2"sq decorative bars.


Acrylic: Cylinder is UL-94 HB Flame Class rated. Top and bottom lens standard.

Standard Finishes: Highly durable oven cured no VOC premium powder coat.

LED Dimming: 1% 0-10V dimming standard with LED lamping option.

Modified: Contact factory for modified lengths, lamping and decorative fronts.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:				
GL-4430-	G-	W-	BLK-	А
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
GL-4430 W in 7 1/4" mm 185 H in 18" mm 460 2.3kg D in 4" mm 100	F. 13LED30 G. 13LED35 H. 13LED40	Standard: W. White Opal Optional: S. Satin White F. Faux Alabaster M. Earth Marble Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Bronze TEZ-Textured Bronze TST-Stone Premium: SA-Satin Aluminum	A. No Options B. Damp Location EL. Emergency LED Consult factory. Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F.

All dimensions are nominal.

Light Source Definition

13LED35 13W 80 50000 1895 35	<u>elvin</u> 000 500
13LED40 13W 80 50000 1895 40	000

Universal Voltage unless otherwise specified.