

LED Driver: Driver must be remotely mounted within 25ft from fixture body.

sales@glighting.com www.glighting.com

HANGER

	1. Cable (Standard)	2. Oversized	3. Vertical Remote Canopy	4. Vertical Integral Canopy
GL-2305 GL-2315	 Driver mounted remotely. (3) Cables & (1) power cord per fixture.	 Drivers mounted inside 12.5" canopy.	 Drivers mounted remotely. (4) Canopies total. (1) Power feed canopy.	 Drivers mounted inside 12.5" canopy. (1) Oversized canopy per fixture. (4) Canopies total. (1) Power feed point.
GL-2306 GL-2316	 (1) Drivers mounted remotely. (3) Cables and (1) power cord per fixture.	 Drivers mounted inside 12.5" canopy.	 Drivers mounted remotely. (4) Canopies total. (1) Power feed canopy.	 Drivers mounted inside 12.5" canopy. (1) Oversized canopy per fixture. (4) Canopies total. (1) Power feed point.
GL-2307 GL-2317	 Drivers mounted remotely. (4) Cables & (1) power cord per fixture.	 Drivers mounted inside 12.5" canopy.	 Drivers mounted remotely. (4) Canopies total. (1) Power feed canopy.	 Drivers mounted inside 12.5" canopy. (1) Oversized canopy per fixture. (4) Canopies total. (1) Power feed point.
GL-2308 GL-2318	 (2) Drivers mounted remotely. (4) Cables and (2) power cords per fixture.	 Drivers mounted inside 14.75" canopy.	 Drivers mounted remotely. (4) Canopies total. (2) Power feed canopies.	 Drivers mounted inside 12.5" canopy. (1) Oversized canopies per fixture. (4) Canopies total. (2) Power feed points.
GL-2309 GL-2319	 (2) Drivers mounted remotely. (4) Cables and (2) power cords per fixture.	 Drivers mounted inside 14.75" canopy.	 Drivers mounted remotely. (4) Canopies total. (2) Power feed canopies.	 Drivers mounted inside 12.5" canopy. (2) Oversized canopies per fixture. (4) Canopies total. (2) Power feed points.
GL-2310 Fixture Built in Three Segments	 Drivers mounted remotely. (6) Cables and (3) power cords per fixture. Fixture shipped in segments. On-site assembly required.	 Drivers mounted inside oversized canopy. GL-2310 16" dia canopy. Fixture shipped in segments. On-site assembly required.	 Drivers mounted remotely. (6) Canopies total. Fixture shipped in segments. On-site assembly required. (3) Power feed canopies.	 Drivers mounted inside 12.5" canopy. (2) Oversized canopies per fixture. (6) Canopies total. Fixture shipped in segments. On-site assembly required. (3) Power feed points.
GL-2311 Fixture Built in Three Segments	 Drivers mounted remotely. (6) Cables and (3) power cords per fixture. Fixture shipped in segments. On-site assembly required.	 Drivers mounted inside oversized canopy. GL-2311 16" dia canopy. Fixture shipped in segments. On-site assembly required.	 Drivers mounted remotely. (6) Canopies total. Fixture shipped in segments. On-site assembly required. (3) Power feed canopies.	 Drivers mounted inside 12.5" canopy. (3) Oversized canopies per fixture. (6) Canopies total. Fixture shipped in segments. On-site assembly required. (3) Power feed points.