

# MARINA II TUNABLE WHITE

## Interior Round Semi-Surface Mount



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**Tunable White:** LED option (TW) features tunable white technology that adjusts from 6500K-2700K. For proper control, fixture needs two 0-10V dimming controls.

**LED Tuning:** CCT tunable using 0-10V wall control. TRIAC, DALI, or DMX available upon request.


**LED Dimming:** Intensity adjustable using 1% 0-10V wall control. TRIAC, DALI, or DMX available upon request.

**Shade:** Standard white fabric shade with integral satin white diffuser. Custom shapes, sizes, and colors available.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.

Standard textured white finish



SAMPLE CATALOG NUMBER: GL-3742-				TW5-	W-	A
MODEL NO.				LAMPING	SHADE	OPTIONS
<b>GL-3742</b>	W in 24"	mm 610	15lbs 7kg	TW5	W White C Cream BL Blue	<b>A.</b> No Options  <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage.
	D in 11.5"	mm 295			BK Black S Stone R Red	
<b>GL-3743</b>	W in 30"	mm 760	18lbs 8kg	TW5	Washable: WW White WC Cream WLG Lt Gray	
	D in 12.5"	mm 320			WGR Gray WBK Black WR Red WBL Blue	
<b>GL-3744</b>	W in 36"	mm 915	20lbs 9kg	TW8		
	D in 13.5"	mm 340				
<b>GL-3745</b>	W in 48"	mm 1220	25lbs 11.5kg	TW8		
	D in 15.5"	mm 395				

All Dimensions are nominal.

### Shade

Standard						
White	Cream	Blue	Stone	Red	Black	
Washable - Trilam						
White	Cream	Light Gray	Gray	Black	Red	Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

### Light Source Definition

Code	Total Wattage	Delivered Lumens	Kelvin
TW5	72	7736	3500-1800
TW8	114	12248	3500-1800

Universal Voltage unless otherwise specified.