

TAHOE II RGB+WHITE

Interior Square Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

RGB+White: LED option (RGB30, RGB35, & RGB40) features a full power white and RGB color changing light source. A second circuit controls the white channel. RGB channel wired DMX ready, full white 1% 0-10V dimming standard.

RGB: LED option features RGB color changing light source. RGB channel wired DMX ready.

DMX: Controls by others.

Static Color: LED options (Red, Green, or Blue) feature static color.

Shade: Standard white fabric shade with integral satin white diffuser.


Custom shapes, sizes, and colors available.



Canopy: Matches fixture finish. Low profile canopy may be mounted on flat or sloped ceilings up to 40°. Available stem or field adjustable cord and cable.

Cable Hanger Option: Supplied with standard 72" white cord and cable. Field adjustable.

Finish: Highly durable oven cured no VOC premium powder coat.

Surge Protection: External surge protector provided as standard.



SAMPLE CATALOG NUMBER:							
GL-2732-	L55-	W-	NSN-	1-	A-	023	
MODEL NO.	LAMPING	SHADE	FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
GL-2732 W in 24" 15lbs D in 11.5" 7kg H in 23"	DD. RED EE. GREEN FF. BLUE GG. RGB*	HH. RGB30* II. RGB35* JJ. RGB40*	W White C Cream BL Blue BK Black S Stone R Red	Standard: Powder Coat BLK -Black BL -Blue GR -Gray LG -Light Gray BE -Beige PAB -Antique Brass PA -Painted Aluminum PTC -Painted Copper WH -White DBZ -Dark Bronze NSN -New Satin Nickel BRN -Brown RD -Red CH -Champagne RG -Reed Green SG -Sungold GM -Gun Metal POR -Oil Rubbed Bronze PG -Pine Green DO -Deep Orange PV -Purple Violet NB -Navy Blue	1. Stem  5. Cord & Cable  Supplied with white cord with hanger option 5.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. LC. 150" Cord & Cable Supplied with 150" Cord & Cable.	Specify overall height for stem hanger option in inches.
GL-2733 W in 30" 18lbs D in 12.5" 8kg H in 24"	KK. RED LL. GREEN MM. BLUE NN. RGB*	OO. RGB30* PP. RGB35* QQ. RGB40*	WW White WC Cream WLG Lt Gray WGR Gray	Textured Powder TLV -Light Verdigris TWH -Textured White TBL -Textured Black TS -Textured Silver TBZ -Textured Bronze TST -Stone			
GL-2734 W in 36" 20lbs D in 13.5" 9kg H in 25"	RR. RED SS. GREEN TT. BLUE UU. RGB*	VV. RGB30* WW. RGB35* XX. RGB40*	WBL Blue				
GL-2735 W in 48" 25lbs D in 15.5" 11.5kg H in 27"	YY. RED ZZ. GREEN AB. BLUE AC. RGB*	AD. RGB30* AE. RGB35* AF. RGB40*					

All Dimensions are nominal.

*DMX controls supplied by others.

Shade

Standard

White Cream Blue Stone Red Black

Washable - Trilam

White Cream Light Gray Gray Black Red Blue

Custom fabrics available upon request. Contact factory. Reproduced graphic representation. Please contact sales@glighting.com for fabric samples.

Light Source Definition

Fixture	Total Wattage	Rated CRI	Rated Life Hrs	Delivered Lumens
GL-2732	72	+80	50000	7436
GL-2733	72	+80	50000	7436
GL-2734	114	+80	50000	12248
GL-2735	114	+80	50000	12248

Universal Voltage unless otherwise specified.