

# BIRMINGHAM

## Indoor Pendant



9777 Reavis Park Drive

St. Louis, MO 63123

800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** GL-2020-2023 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:							
GL-2022-		L95-	S-	NSN-	1-	A-	038
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT	
<b>GL-2020</b> 14lbs B in 18" mm 460 6 kg W in 21" mm 535 D in 7" mm 180 H in 29" mm 740	<b>IN3. 3MED</b> <b>L50. 5LED30</b> <b>L55. 5LED35</b> <b>L54. 5LED40</b>	<b>Standard:</b> S. Satin White  <b>Optional:</b> W. White Opal	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	<b>1. Stem</b>  <b>2. Cable</b>  <b>3. Arms</b>  <b>4. Stem Cluster</b>  Custom lengths available. For heights longer than standard, additional length will be added to top stem.	<b>A. No Options</b> <b>F1. Add Finial</b>  <b>F2. Add Finial</b>  <b>B. Damp Location</b> Available in powder coat or Satin Aluminum finish. <b>EL. Emergency LED</b> Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. <b>W. White Opal Top Lens</b> INC only <b>C. Clear Top Lens</b> INC only <b>P. Perforated Top Lens</b> INC only Multi-circuiting available upon request.	Standard overall height shown by model no.  For custom overall height, specify in inches.	
<b>GL-2021</b> 21lbs B in 24" mm 610 10 kg W in 27" mm 685 D in 8" mm 205 H in 34" mm 865	<b>IN3. 3MED</b> <b>L60. 6LED30</b> <b>L65. 6LED35</b> <b>L64. 6LED40</b>	Acrylic is UL-94 HB Flame Class rated.	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	
<b>GL-2022</b> 29lbs B in 30" mm 760 13kg W in 33 1/2" mm 850 D in 10" mm 255 H in 38" mm 965	<b>IN6. 6MED</b> <b>L90. 9LED30</b> <b>L95. 9LED35</b> <b>L94. 9LED40</b>	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	
<b>GL-2023</b> 37lbs B in 38" mm 965 17kg W in 41" mm 1040 D in 10 1/2" mm 265 H in 42" mm 1070	<b>IN6. 6MED</b> <b>L120. 12LED30</b> <b>L125. 12LED35</b> <b>L124. 12LED40</b>  38" available in Satin Aluminum and powder coat finish only	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	(Same as GL-2020)	

Fixtures over 50 lbs require reinforced junction box  
 All dimensions are nominal.

### Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Kelvin	Delivered Lumens
IN3, IN6	Med	A-19	Medium 120V	L60	87	3000	10544
				L65	87	3500	10544
				L64	87	4000	10544
				L90	130	3000	16400
				L95	130	3500	16400
				L94	130	4000	16400
				L120	177	3000	21794
				L125	177	3500	21794
				L124	177	4000	21794

Contact factory for availability of other lamp configurations.

Universal Voltage unless otherwise specified.