

# BRISTOL

## Indoor Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.
- LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.
- Body:** GL-2030-2033 rings spun in 18ga steel or .050 aluminum. Closed body with LED lamping.
- Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:								
GL-2032-		L95-		S-	NSN-	1-	A-	038
MODEL NO.	LAMPING		ACRYLIC	FINISH	HANGER	OPTION(S)		OVERALL HEIGHT
<b>GL-2030</b> 14lbs B in 18" mm 460 6 kg W in 23 1/4" mm 590 D in 6 1/8" mm 155 H in 29" mm 740	IN3. 3MED	L50. 5LED30 L55. 5LED35 L54. 5LED40	<b>Standard:</b> S. Satin White  <b>Optional:</b> W. White Opal	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	1. Stem  2. Cable  3. Arms  4. Stem Cluster  <small>Custom lengths available. For heights longer than standard, additional length will be added to top stem.</small>	<b>A. No Options</b> <b>F1. Add Finial</b>  <b>F2. Add Finial</b>  <b>B. Damp Location</b> <small>Available in powder coat or Satin Aluminum finish.</small> <b>EL. Emergency LED</b> <small>Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only.</small> <b>P. Perforated Top Lens</b> <small>INC only</small> <small>Multi-circuiting available upon request.</small>	Standard overall height shown by model no.  For custom overall height, specify in inches.	
<b>GL-2031</b> 21lbs B in 24" mm 610 10 kg W in 30 5/8" mm 780 D in 6 1/2" mm 165 H in 34" mm 865	IN3. 3MED	L60. 6LED30 L65. 6LED35 L64. 6LED40	Acrylic is UL-94 HB Flame Class rated.	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	
<b>GL-2032</b> 29lbs B in 30" mm 760 13kg W in 36 1/4" mm 920 D in 6 7/8" mm 170 H in 38" mm 965	IN6. 6MED	L90. 9LED30 L95. 9LED35 L94. 9LED40	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	
<b>GL-2033</b> 37lbs B in 38" mm 965 17kg W in 44 7/8" mm 1140 D in 8 5/8" mm 220 H in 42" mm 1070	IN6. 6MED	L120. 12LED30 L125. 12LED35 L124. 12LED40	38" available in Satin Aluminum and powder coat finish only	Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	(Same as GL-2030)	(Same as GL-2030)	(Same as GL-2030)	

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Kelvin	Delivered Lumens	CRI
IN3, IN6	Med	A-19	Medium 120V	L60	78	3000	10544	+90
				L65	78	3500	10544	+90
				L64	78	4000	10544	+90
				L90	118	3000	16400	+90
				L95	118	3500	16400	+90
				L94	118	4000	16400	+90
				L120	157	3000	21794	+90
				L125	157	3500	21794	+90
				L124	157	4000	21794	+90

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.

