

CAMBRIDGE

Indoor Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@lighting.com www.lighting.com

GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.
- LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.
- Body:** GL-2100-2103 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.
- Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



Textured white pan with LED lamping



SAMPLE CATALOG NUMBER:								
GL-2102-		L95-		S-	NSN-	1-	A-	038
MODEL NO.	LAMPING		ACRYLIC	FINISH	HANGER	OPTION(S)		OVERALL HEIGHT
GL-2100 14lbs B in 18" mm 460 6 kg W in 21" mm 535 D in 6 1/8" mm 155 H in 29" mm 740	IN3. 3MED	L50. 5LED30 L55. 5LED35 L54. 5LED40	Standard: s. Satin White Optional: W. White Opal	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	1. Stem 2. Cable 3. Arms 4. Stem Cluster <small>Custom lengths available. For heights longer than standard, additional length will be added to top stem.</small>	A. No Options F1. Add Finial F2. Add Finial B. Damp Location Available in powder coat or Satin Aluminum finish. EL. Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. P. Perforated Top Lens INC only Multi-circuiting available upon request.	Standard overall height shown by model no. For custom overall height, specify in inches.	
GL-2101 21lbs B in 24" mm 610 10 kg W in 27 1/8" mm 690 D in 6 1/2" mm 165 H in 34" mm 865	IN3. 3MED	L60. 6LED30 L65. 6LED35 L64. 6LED40	Acrylic is UL-94 HB Flame Class rated.					
GL-2102 29lbs B in 30" mm 760 13kg W in 33 1/2" mm 850 D in 7" mm 180 H in 38" mm 965	IN6. 6MED	L90. 9LED30 L95. 9LED35 L94. 9LED40						
GL-2103 37lbs B in 38" mm 965 17kg W in 42" mm 1065 D in 9" mm 230 H in 42" mm 1070	IN6. 6MED	L120. 12LED30 L125. 12LED35 L124. 12LED40	38" available in Satin Aluminum and powder coat finish only	Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone				

Fixtures over 50 lbs require reinforced junction box
All dimensions are nominal.

Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Kelvin	Delivered Lumens	CRI
IN3, IN6	Med	A-19	Medium 120V	L60	78	3000	10544	+90
				L65	78	3500	10544	+90
				L64	78	4000	10544	+90
				L90	118	3000	16400	+90
				L95	118	3500	16400	+90
				L94	118	4000	16400	+90
				L120	157	3000	21794	+90
				L125	157	3500	21794	+90
				L124	157	4000	21794	+90

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

