

# CENTRIC

## Interior Surface Mount






9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency 90 CRI mid-power LEDs. Universal voltage.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, and DMX available upon request.
- Direct to Ceiling Mount:** Ceiling mounting plate location is within the fixture body and not seen in final installation.
- Junction Box Mount:** Ceiling mounting plate extends .125" from the fixture body with a round 5" junction box cover.
- LED Driver:** Must be remotely mounted within 25ft from fixture body.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for modified fixture sizes and lumen packages.
- Surge Protection:** External surge protector provided as standard.



| SAMPLE CATALOG NUMBER:                                 |  |   |  |   |
|--|--|---|--|---|
| GL-3307-   | B-   | RD-   | 1-   | A   |
| MODEL NO.  | LAMPING  | FINISH  | MOUNTING   | OPTIONS   |
| <b>GL-3305</b> W in 24"<br>5lbs B in 3" x 3"<br>2.2kg  | <b>A.</b> LED30<br><b>B.</b> LED35<br><b>C.</b> LED40<br><b>D.</b> LED30LO<br><b>E.</b> LED35LO<br><b>F.</b> LED40LO | <b>Standard:</b><br>Powder Coat<br><b>BLK</b> -Black<br><b>BL</b> -Blue<br><b>GR</b> -Gray<br><b>LG</b> -Light Gray<br><b>BE</b> -Beige<br><b>PAB</b> -Antique Brass<br><b>PA</b> -Painted Aluminum<br><b>PTC</b> -Painted Copper<br><b>WH</b> -White<br><b>DBZ</b> -Dark Bronze<br><b>NSN</b> -New Satin Nickel<br><b>BRN</b> -Brown<br><b>RD</b> -Red<br><b>CH</b> -Champagne<br><b>RG</b> -Reed Green<br><b>SG</b> -Sungold<br><b>GM</b> -Gun Metal<br><b>POR</b> -Oil Rubbed Bronze<br><b>PG</b> -Pine Green<br><b>DO</b> -Deep Orange<br><b>PV</b> -Purple Violet<br><b>NB</b> -Navy Blue<br><br><b>Textured Powder</b><br><b>TLV</b> -Light Verdigris<br><b>TWH</b> -Textured White<br><b>TBL</b> -Textured Black<br><b>TS</b> -Textured Silver<br><b>TBZ</b> -Textured Bronze<br><b>TST</b> -Stone | <b>1. Direct to Ceiling</b><br><br>Drivers mounted remotely<br><br><b>2. Junction Box Mount</b><br><br>Drivers mounted remotely. (1) 5in junction box cover plate. | <b>A.</b> No Options<br><br><b>EL.</b> Emergency LED<br>Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. |
| <b>GL-3306</b> W in 36"<br>8lbs B in 3" x 3"<br>3.6kg  |  |   |  |   |
| <b>GL-3307</b> W in 48"<br>12lbs B in 3" x 3"<br>5.4kg |  |   |  |   |
| <b>GL-3308</b> W in 60"<br>14lbs B in 3" x 3"<br>6.3kg |  |   |  |   |
| <b>GL-3309</b> W in 72"<br>18lbs B in 3" x 3"<br>8.2kg |  |   |  |   |

All Dimensions are nominal.

### Light Source Definition

| High Lumen Output |               |           |                |                  |                | Low Lumen Output |               |           |                |                  |                |
|-------------------|---------------|-----------|----------------|------------------|----------------|------------------|---------------|-----------|----------------|------------------|----------------|
| Fixture           | Total Wattage | Rated CRI | Rated Life Hrs | Delivered Lumens | Kelvin         | Code             | Total Wattage | Rated CRI | Rated Life Hrs | Delivered Lumens | Kelvin         |
| GL-3305           | 52            | +90       | 50000          | 4518             | 3000/3500/4000 | GL-3305          | 28            | +90       | 50000          | 2788             | 3000/3500/4000 |
| GL-3306           | 72            | +90       | 50000          | 6694             | 3000/3500/4000 | GL-3306          | 42            | +90       | 50000          | 4419             | 3000/3500/4000 |
| GL-3307           | 102           | +90       | 50000          | 9355             | 3000/3500/4000 | GL-3307          | 59            | +90       | 50000          | 6120             | 3000/3500/4000 |
| GL-3308           | 122           | +90       | 50000          | 11269            | 3000/3500/4000 | GL-3308          | 70            | +90       | 50000          | 7364             | 3000/3500/4000 |
| GL-3309           | 145           | +90       | 50000          | 13427            | 3000/3500/4000 | GL-3309          | 84            | +90       | 50000          | 8855             | 3000/3500/4000 |

Universal Voltage unless otherwise specified.