

DAYTONA

Interior Pendant




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency 90CRI mid-power LEDs. Universal voltage.
- Uplight:** Optional uplight is wired on a second circuit.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Driver:** Must be mounted within 25ft from fixture body.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Canopy:** Matches fixture finish.
- Cable Hanger:** Standard 150" cable and white cord for on-site adjustability.
- Modifications:** Consult factory for modified fixture sizes and lumen packages.
- Surge Protection:** External surge protector provided as standard.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, and DMX available upon request.



SAMPLE CATALOG NUMBER:		B-	B-	BLK-	1-	A
MODEL NO.		LAMPING		FINISH	HANGER	OPTIONS
GL-2955	W in 24" 5lbs B in 3" 3.2kg H in 11"-145"	Down: A. LED30 B. LED35 C. LED40 D. LED30LO E. LED35LO F. LED40LO	Up: A. LED30 B. LED35 C. LED40 D. LED30LO E. LED35LO F. LED40LO G. NONE	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	1. Cable - Standard Drivers mounted remotely. 2. Oversized Drivers mounted inside oversized canopy. 3. Vertical Remote Canopy Drivers mounted remotely. 4. Vertical Integral Canopy Drivers mounted inside 12.5" oversized canopy. Hanger options 1&3 supplied with remote driver box.	A. No Options BC. Black Cord Fixture supplied with black power cord. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-2956	W in 30" 10lbs B in 3" 4.5kg H in 11"-145"					
GL-2957	W in 36" 14lbs B in 3" 6.3kg H in 18.75"-145"					

All Dimensions are nominal.

Light Source Definition

Fixture	High Lumen Output					Low Lumen Output					
	Total Wattage	Rated CRI	Delivered Life Hrs	Lumens	Kelvin	Code	Total Wattage	Rated CRI	Delivered Life Hrs	Lumens	Kelvin
GL-2955	45	+90	50000	4281	3000/3500/4000	GL-2955	24	+90	50000	2355	3000/3500/4000
GL-2956	64	+90	50000	6092	3000/3500/4000	GL-2956	35	+90	50000	3351	3000/3500/4000
GL-2957	84	+90	50000	7903	3000/3500/4000	GL-2957	46	+90	50000	4347	3000/3500/4000

Wattage & lumens represent output for one side (up or down).

Universal Voltage unless otherwise specified.