

# DOVER

## Interior Pendant






9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency 90 CRI mid-power LEDs. Universal voltage.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, and DMX available upon request.
- Acrylic:** High diffusion and consistent light transmission.
- Driver:** Must be mounted within 25ft from fixture body.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Canopy:** Matches fixture finish.
- Cable Hanger:** Standard 150" cable and white cord for on-site adjustability.
- Modifications:** Consult factory for modified fixture sizes and lumen packages.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-2940-		B-	BLK-	3-	A
MODEL NO.		LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2940</b> W in 18"x36" 5lbs B in 3" 3.2kg H in 11"-145"		Down: <b>A. LED30</b> <b>B. LED35</b> <b>C. LED40</b> <b>D. LED30LO</b> <b>E. LED35LO</b> <b>F. LED40LO</b>	Standard: Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  Textured Powder <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Textured Stone	<b>3. Vertical Remote Canopy</b>  Drivers mounted remotely.	<b>A. No Options</b> <b>BC. Black Cord</b> Fixture supplied with black power cord. <b>EL. Emergency LED</b> Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-2941</b> W in 24"x48" 7lbs B in 3" 3.2kg H in 11"-145"				<b>4. Vertical Integral Canopy</b>  Drivers mounted inside 12.5" oversized canopy.	
<b>GL-2942</b> W in 30"x60" 10lbs B in 3" 4.5kg H in 18.75"-145"				Hanger options 3 supplied with remote driver box.	

All Dimensions are nominal.

### Light Source Definition

High Lumen Output						Low Lumen Output					
Fixture	Total Wattage	Rated CRI	Life Hrs	Delivered Lumens	Kelvin	Fixture	Total Wattage	Rated CRI	Life Hrs	Delivered Lumens	Kelvin
GL-2940	56	+90	50000	4775	3000/3500/4000	GL-2940	33	+90	50000	2865	3000/3500/4000
GL-2941	106	+90	50000	9005	3000/3500/4000	GL-2941	63	+90	50000	5403	3000/3500/4000
GL-2942	173	+90	50000	14362	3000/3500/4000	GL-2942	103	+90	50000	8617	3000/3500/4000

Universal Voltage unless otherwise specified.

