

# HUDSON

## Interior Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** GL-2260-2262 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.



**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless flat bottom acrylic drum is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2262-	L95-	S-	NSN-	1-	A-	038		
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT		
<b>GL-2260</b> 14lbs B in 18" mm 460 6 kg W in 24" mm 610 D in 8" mm 200 H in 29" mm 740	<b>IN3. 3MED</b> <b>L50. 5LED30</b> <b>L55. 5LED35</b> <b>L54. 5LED40</b>	<b>Standard:</b> S. Satin White <b>Optional:</b> W. White Opal  Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue  <b>Textured Powder</b> TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	<b>1. Stem</b>  <b>2. Cable</b>  <b>3. Arms</b>  <b>4. Stem Cluster</b>  Custom lengths available. For heights longer than standard, additional length will be added to top stem.	<b>A. No Options</b> <b>F1. Add Finial</b>  <b>F2. Add Finial</b>  <b>B. Damp Location</b> Available in powder coat or Satin Aluminum finish. <b>EL. Emergency LED</b> Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. <b>W. White Opal Top Lens</b> INC only <b>C. Clear Top Lens</b> INC only <b>P. Perforated Top Lens</b> INC only Multi-circuiting available upon request.	Standard overall height shown by model no.  For custom overall height, specify in inches.		
							<b>GL-2261</b> 21lbs B in 24" mm 610 10 kg W in 30" mm 765 D in 9" mm 230 H in 34" mm 865	<b>IN3. 3MED</b> <b>L60. 6LED30</b> <b>L65. 6LED35</b> <b>L64. 6LED40</b>
							<b>GL-2262</b> 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 10" mm 255 H in 38" mm 965	<b>IN6. 6MED</b> <b>L90. 9LED30</b> <b>L95. 9LED35</b> <b>L94. 9LED40</b>

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Delivered Kelvin	Delivered Lumens	CRI
IN3, IN6	Med	A-19	Medium	L50	65	3000	8971	+90
				L55	65	3500	8971	+90
				L54	65	4000	8971	+90
				L60	78	3000	10544	+90
				L65	78	3500	10544	+90
				L64	78	4000	10544	+90
				L90	118	3000	16400	+90
				L95	118	3500	16400	+90
				L94	118	4000	16400	+90

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.