

# PLYMOUTH

## Indoor Pendant



9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

**LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.

**LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.


**Body:** GL-2170-2173 ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.

**Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.

**Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.

**Finish:** Highly durable oven cured no VOC premium powder coat.

**Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:								
GL-2172-		L95-		S-	NSN-	1-	A-	038
MODEL NO.	LAMPING		ACRYLIC	FINISH	HANGER	OPTION(S)		OVERALL HEIGHT
<b>GL-2170</b> 14lbs B in 18" mm 460 6 kg W in 24" mm 610 D in 6" mm 150 H in 29" mm 740	<b>IN3. 3MED</b>	<b>L50. 5LED30</b> <b>L55. 5LED35</b> <b>L54. 5LED40</b>	<b>Standard:</b> S. Satin White  <b>Optional:</b> W. White Opal	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue	<b>1. Stem</b>  <b>2. Cable</b>  <b>3. Arms</b>  <b>4. Stem Cluster</b> 	<b>A. No Options</b> <b>F1. Add Finial</b>  <b>F2. Add Finial</b>  <b>B. Damp Location</b> Available in powder coat or Satin Aluminum finish. <b>EL. Emergency LED</b> Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. <b>P. Perforated Top Lens</b> INC only	Standard overall height shown by model no.  For custom overall height, specify in inches.	
<b>GL-2171</b> 21lbs B in 24" mm 610 10 kg W in 30" mm 765 D in 6 1/2" mm 165 H in 34" mm 865	<b>IN3. 3MED</b>	<b>L60. 6LED30</b> <b>L65. 6LED35</b> <b>L64. 6LED40</b>	Acrylic is UL-94 HB Flame Class rated.	<b>Textured Powder</b> TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	Custom lengths available. For heights longer than standard, additional length will be added to top stem.			
<b>GL-2172</b> 29lbs B in 30" mm 760 13kg W in 36" mm 915 D in 7" mm 180 H in 38" mm 965	<b>IN6. 6MED</b>	<b>L90. 9LED30</b> <b>L95. 9LED35</b> <b>L94. 9LED40</b>						
<b>GL-2173</b> 37lbs B in 38" mm 965 17kg W in 44" mm 1120 D in 8 1/2" mm 215 H in 42" mm 1070	<b>IN6. 6MED</b>	<b>L120. 12LED30</b> <b>L125. 12LED35</b> <b>L124. 12LED40</b>	38" available in Satin Aluminum and powder coat finish only					

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Kelvin	Delivered Lumens	CRI
IN3, IN6	Med	A-19	Medium 120V	L60	78	3000	10544	+90
				L65	78	3500	10544	+90
				L64	78	4000	10544	+90
				L90	118	3000	16400	+90
				L95	118	3500	16400	+90
				L94	118	4000	16400	+90
				L120	157	3000	21794	+90
				L125	157	3500	21794	+90
				L124	157	4000	21794	+90

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.

