

# ROTOR

## Interior Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency 90 CRI mid-power LEDs. Universal voltage.
- Lower Output:** Lamping code ending with LO features lower lumen output.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, and DMX available upon request.
- Acrylic:** High diffusion and consistent light transmission.
- Driver:** Must be mounted within 25ft from fixture body.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Canopy:** Matches fixture finish.
- Cable Hanger:** Standard 150" cable and white cord for on-site adjustability.
- Modifications:** Consult factory for modified fixture sizes and lumen packages.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:		B-	BLK-	1-	A
GL-2950-		LAMPING	FINISH	HANGER	OPTIONS
<b>GL-2950</b>	W in 24" 5lbs B in 3" 3.2kg H in 11"-145"	<b>A.</b> LED30 <b>B.</b> LED35 <b>C.</b> LED40 <b>D.</b> LED30LO <b>E.</b> LED35LO <b>F.</b> LED40LO	<b>Standard:</b> Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>PG-</b> Pine Green <b>DO-</b> Deep Orange <b>PV-</b> Purple Violet <b>NB-</b> Navy Blue  <b>Textured Powder</b> <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBZ-</b> Textured Bronze <b>TST-</b> Stone	<b>1. Cable - Standard</b>  Drivers mounted remotely. <b>2. Oversized</b>  Drivers mounted inside oversized canopy. <b>3. Vertical Canopy</b>  Drivers mounted remotely. <b>4. Vertical Integral Canopy</b>  Drivers mounted inside oversized canopy.  Hanger options 1&3 supplied with remote driver box.	<b>A.</b> No Options <b>BC.</b> Black Cord Fixture supplied with black power cord. <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
<b>GL-2951</b>	W in 30" 10lbs B in 3" 4.5kg H in 11"-145"				
<b>GL-2952</b>	W in 36" 14lbs B in 3" 6.3kg H in 18.75"-145"				

All Dimensions are nominal.

### Light Source Definition

High Lumen Output						Low Lumen Output					
Fixture	Total Wattage	Rated CRI	Life Hrs	Delivered Lumens	Kelvin	Code	Total Wattage	Rated CRI	Life Hrs	Delivered Lumens	Kelvin
GL-2950	40	+90	50000	3307	3000/3500/4000	GL-2950	24	+90	50000	1985	3000/3500/4000
GL-2951	63	+90	50000	5279	3000/3500/4000	GL-2951	37	+90	50000	3168	3000/3500/4000
GL-2952	91	+90	50000	7557	3000/3500/4000	GL-2952	54	+90	50000	4535	3000/3500/4000

Universal Voltage unless otherwise specified.

