

# WESTFIELD

## Indoor Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable. Universal voltage.
- LED Dimming:** Standard 1% 0-10V dimming with LED lamping option.
- Body:** Ring spun in 18ga steel or .050 aluminum. Closed body with LED lamping.
- Canopy:** Low profile. May be mounted on flat or sloped ceilings up to 40°.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



### SAMPLE CATALOG NUMBER:

MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
<b>GL-2300</b> 14lbs B in 18" mm 460 6 kg W in 22 3/8" mm 570 D in 9 1/2" mm 240 H in 29" mm 740	<b>IN3.3MED L50.5LED30</b> <b>L55.5LED35</b> <b>L54.5LED40</b>	<b>Standard:</b> S. Satin White <b>Optional:</b> W. White Opal	<b>Standard:</b> Powder Coat <b>BLK-Black</b> <b>BL-Blue</b> <b>GR-Gray</b> <b>LG-Light Gray</b> <b>BE-Beige</b> <b>PAB-Antique Brass</b> <b>PA-Painted Aluminum</b> <b>PTC-Painted Copper</b> <b>WH-White</b> <b>DBZ-Dark Bronze</b> <b>NSN-New Satin Nickel</b> <b>BRN-Brown</b> <b>RD-Red</b> <b>CH-Champagne</b> <b>RG-Reed Green</b> <b>SG-Sungold</b> <b>GM-Gun Metal</b> <b>POR-Oil Rubbed Bronze</b> <b>PG-Pine Green</b> <b>DO-Deep Orange</b> <b>PV-Purple Violet</b> <b>NB-Navy Blue</b>	<b>1. Stem</b> <b>2. Cable</b> <b>3. Arms</b> <b>4. Stem Cluster</b>	<b>A. No Options</b> <b>F1. Add Finial</b> <b>F2. Add Finial</b> <b>B. Damp Location</b> Available in powder coat or Satin Aluminum finish. <b>EL. Emergency LED</b> Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. <b>W. White Opal Top Lens</b> INC only <b>C. Clear Top Lens</b> INC only <b>P. Perforated Top Lens</b> INC only Multi-circuiting available upon request.	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2301</b> 21lbs B in 24" mm 610 10 kg W in 29 1/2" mm 750 D in 10 1/2" mm 265 H in 34" mm 865	<b>IN3.3MED L60.6LED30</b> <b>L65.6LED35</b> <b>L64.6LED40</b>	Acrylic is UL-94 HB Flame Class rated.				
<b>GL-2302</b> 29lbs B in 30" mm 760 13kg W in 34 3/8" mm 875 D in 11 1/2" mm 290 H in 38" mm 965	<b>IN6.6MED L90.9LED30</b> <b>L95.9LED35</b> <b>L94.9LED40</b>					
<b>GL-2303</b> 37lbs B in 38" mm 965 17kg W in 42 7/8" mm 1090 D in 13" mm 330 H in 42" mm 1070	<b>IN6.6MED L120.12LED30</b> <b>L125.12LED35</b> <b>L124.12LED40</b>  38" available in Satin Aluminum and powder coat finish only		<b>Textured Powder</b> <b>TLV-Light Verdigris</b> <b>TWH-Textured White</b> <b>TBL-Textured Black</b> <b>TS-Textured Silver</b> <b>TBZ-Textured Bronze</b> <b>TST-Stone</b>			

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Lamp Definition

Code	Lamp	Type	Lamp Base	Code	Total Wattage	Kelvin	Delivered Lumens	CRI
IN3, IN6	Med	A-19	Medium 120V	L60	78	3000	10544	+90
				L65	78	3500	10544	+90
				L64	78	4000	10544	+90
				L90	118	3000	16400	+90
				L95	118	3500	16400	+90
				L94	118	4000	16400	+90
				L120	157	3000	21794	+90
				L125	157	3500	21794	+90
				L124	157	4000	21794	+90

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.