

# CHRONICLE

## Outdoor Sconce





9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable.
- LED Dimming:** 1% 0-10V dimming standard with LED lamping option.
- Body:** Formed .050 Al body with 1/4" x 1/2" Al rails and 1/2"sq decorative bars.
- Acrylic:** Cylinder is UL-94 HB Flame Class rated. Top and bottom lens standard.
- Standard Finishes:** Highly durable oven cured no VOC premium powder coat.
- Modified:** Contact factory for modified lengths, lamping and decorative fronts.
- Surge Protection:** External surge protector provided as standard.
- Listing:** Fixture ETL listed for wet locations.



SAMPLE CATALOG NUMBER:				
GL-5410-	G-	W-	NSN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)
<b>GL-5410</b> W in 7 1/4" mm 185 H in 18" mm 460 5lbs 2.3kg D in 4 3/4" mm 120	<b>F.</b> 13LED30 <b>G.</b> 13LED35 <b>H.</b> 13LED40	<b>Standard:</b> W. White Opal <b>Optional:</b> S. Satin White Acrylic is UL-94 HB Flame Class rated.	<b>Standard:</b> Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	<b>A. No Options</b> <b>EL. Emergency LED</b> Consult factory. Must be remotely mounted in a controlled environment with an area temperature range of 32°- 131°F. <b>F. LED Up Light 4000K</b> Metal cap standard with option. Consult factory for dimming. <b>G. LED Down Light 4000K</b> Metal cap standard with option. Consult factory for dimming. <b>H. LED Up Light 3000K</b> Metal cap standard with option. Consult factory for dimming. <b>I. LED Down Light 3000K</b> Metal cap standard with option. Consult factory for dimming.

All dimensions are nominal.

### Light Source Definition

Lamp	LED	CRI	Rated Life Hrs	Delivered Lumens	Kelvin
13LED30	13W	+90	50000	1192	3000
13LED35	13W	+90	50000	1192	3500
13LED40	13W	+90	50000	1192	4000
UP/DOWN	4W SPOT LIGHT	80	35000	260	3000 or 4000

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.