

CONE

Exterior Pendant






9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Listing:** ETL listed for wet locations.
- Canopy:** Matches fixture finish. Hanger 3 includes 10.125" dia by 2.625" H spinning.
- Driver:** Max remote driver installation distance 25ft from fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-5350-		E-	BLK-	1-	A	038
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT	
GL-5350 8lbs W 16" 3.6kg B 11" H 38"	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue	1. Stem Mount Remote Driver  Drivers mounted remotely 3. Stem Mount Oversized Canopy  Drivers mounted inside oversized canopy	A. No Options EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Specify overall height in inches.	
GL-5351 10lbs W 24" 4.5kg B 15 3/8" H 42"	G. 1LED30 H. 1LED35 I. 1LED40 J. 1LED30 K. 1LED35 L. 1LED40 M. 1LED30 N. 1LED35 O. 1LED40	Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone				

All Dimensions are nominal.

Light Source Definition

Downlight Output						
Code	LED	Wattage	Total Lumens	Delivered Lumens	Kelvin	CRI
A	1LED30	17W	1534	1534	3000	80
B	1LED35	17W	1534	1534	3500	80
C	1LED40	17W	1534	1534	4000	80
D	1LED30	24W	2148	2148	3000	80
E	1LED35	24W	2148	2148	3500	80
F	1LED40	24W	2148	2148	4000	80
G	1LED30	15W	1361	1361	3000	80
H	1LED35	15W	1361	1361	3500	80
I	1LED40	15W	1361	1361	4000	80
J	1LED30	26W	2334	2334	3000	80
K	1LED35	26W	2334	2334	3500	80
L	1LED40	26W	2334	2334	4000	80
M	1LED30	39W	3501	3501	3000	80
N	1LED35	39W	3501	3501	3500	80
O	1LED40	39W	3501	3501	4000	80

Universal Voltage unless otherwise specified.
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

