

CONE

Interior Surface Mount




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Driver:** Integral in fixture body. Remote driver required for V,W,X lamping options.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Inner Finish:** Inner finish available in white, black, and gold liquid paint.
- Non-white inner finishes will reduce lumen output.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:

GL-3350-

MODEL NO.	E-	BLK-	MO-	A
MODEL NO.	LAMPING	OUTER FINISH	INNER FINISH	OPTIONS
GL-3350 8lbs W in 16" 3.6kg H in 11"	A. 1LED30 B. 1LED35 C. 1LED40 D. 1LED30 E. 1LED35 F. 1LED40	Standard: Powder Coat BLK-Black BL-Blue GR-Gray LG-Light Gray BE-Beige PAB-Antique Brass PA-Painted Aluminum PTC-Painted Copper WH-White DBZ-Dark Bronze NSN-New Satin Nickel BRN-Brown RD-Red CH-Champagne RG-Reed Green SG-Sungold GM-Gun Metal POR-Oil Rubbed Bronze PG-Pine Green DO-Deep Orange PV-Purple Violet NB-Navy Blue Textured Powder TLV-Light Verdigris TWH-Textured White TBL-Textured Black TS-Textured Silver TBZ-Textured Bronze TST-Stone	Standard: MO-Matches Outer Finish Liquid Paint WH-White BLK-Black GL-Gold	A. No Options DM. DMX Dimming Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. EL. Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.
GL-3351 10lbs W in 24" 4.5kg H in 15 3/8"	G. 1LED30 H. 1LED35 I. 1LED40 J. 1LED30 K. 1LED35 L. 1LED40 M. 1LED30 N. 1LED35 O. 1LED40 V. 1LED30* W. 1LED35* X. 1LED40*			
	*Remote Driver only.	Outer finish designated by first finish code.	Inner finish designated by second finish code.	

All Dimensions are nominal.

Light Source Definition

Downlight Output						Downlight Output					
Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI	Code	LED	Total Wattage	Delivered Lumens	Kelvin	CRI
A	1LED30	17W	1534	3000	80	V	1LED30	68W	5076*	3000	80
B	1LED35	17W	1534	3500	80	W	1LED35	68W	5076*	3500	80
C	1LED40	17W	1534	4000	80	X	1LED40	68W	5076*	4000	80
D	1LED30	24W	2148	3000	80						
E	1LED35	24W	2148	3500	80						
F	1LED40	24W	2148	4000	80						
G	1LED30	15W	1361	3000	80						
H	1LED35	15W	1361	3500	80						
I	1LED40	15W	1361	4000	80						
J	1LED30	26W	2334	3000	80						
K	1LED35	26W	2334	3500	80						
L	1LED40	26W	2334	4000	80						
M	1LED30	39W	3501	3000	80						
N	1LED35	39W	3501	3500	80						
O	1LED40	39W	3501	4000	80						

Universal Voltage unless otherwise specified.

Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.

