

# CROSSROAD

## Indoor Pendant




9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable.
- LED Dimming:** 1% 0-10V dimming standard with LED lamping option.
- Body:** Body formed with 18ga steel.
- Canopy:** Low profile. Mounted on flat or sloped ceilings up to 40°.
- Acrylic:** UL-94 HB Flame Class rated.
- Modifications:** Consult factory for lamping, cluster, or sizing options.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:						
GL-2607-	L125-	W-	NSN-	1-	A-	045
MODEL NO.	LAMPING	ACRYLIC	FINISH	HANGER	OPTION(S)	OVERALL HEIGHT
<b>GL-2605</b> 21lbs W in 24" mm 610 10kg D in 9" mm 225 H in 36" mm 915	<b>L60.</b> 6LED30 <b>IN4.</b> 4MED <b>L65.</b> 6LED35 <b>L64.</b> 6LED40	Standard: <b>W.</b> White Opal  Optional: <b>S.</b> Satin White  Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat <b>BLK-</b> Black <b>BL-</b> Blue <b>GR-</b> Gray <b>LG-</b> Light Gray <b>BE-</b> Beige <b>PAB-</b> Antique Brass <b>PA-</b> Painted Aluminum <b>PTC-</b> Painted Copper <b>WH-</b> White <b>DBZ-</b> Dark Bronze <b>NSN-</b> New Satin Nickel <b>BRN-</b> Brown <b>RD-</b> Red <b>CH-</b> Champagne <b>RG-</b> Reed Green <b>SG-</b> Sungold <b>GM-</b> Gun Metal <b>POR-</b> Oil Rubbed Bronze <b>PG-</b> Pine Green <b>DO-</b> Deep Orange <b>PV-</b> Purple Violet <b>NB-</b> Navy Blue  Textured Powder <b>TLV-</b> Light Verdigris <b>TWH-</b> Textured White <b>TBL-</b> Textured Black <b>TS-</b> Textured Silver <b>TBZ-</b> Textured Bronze <b>TST-</b> Stone	1. Stem 2. Cable 3. Arms 4. Stem Cluster  Custom lengths available. For heights longer than standard, additional length will be added to top stem.	<b>A.</b> No Options <b>B.</b> Damp Location Available in powder coat finish. <b>EL.</b> Emergency LED Remote mount up to 10' from lamping in controlled environment with an area temperature range of 32°-131°F. LED only. Specify 120 or 277 voltage. <b>W.</b> White Opal Top Lens INC only <b>C.</b> Clear Top Lens INC only <b>P.</b> Perforated Top Lens INC only	Standard overall height shown by model no.  For custom overall height, specify in inches.
<b>GL-2606</b> 28lbs W in 30" mm 760 13kg D in 10 1/2" mm 265 H in 40" mm 1020	<b>L80.</b> 8LED30 <b>IN4.</b> 4MED <b>L85.</b> 8LED35 <b>L84.</b> 8LED40					
<b>GL-2607</b> 37lbs W in 36" mm 915 17kg D in 12 1/8" mm 310 H in 45" mm 1140	<b>L120.</b> 12LED30 <b>IN4.</b> 4MED <b>L125.</b> 12LED35 <b>IN6.</b> 6MED <b>L124.</b> 12LED40					
<b>GL-2608</b> 52lbs W in 46" mm 1170 24kg D in 14 3/4" mm 375 H in 50" mm 1270	<b>L120.</b> 12LED30 <b>IN6.</b> 6MED <b>L125.</b> 12LED35 <b>IN8.</b> 8MED <b>L124.</b> 12LED40					

Fixtures over 50 lbs require reinforced junction box  
All dimensions are nominal.

### Light Source Definition

Code	Total Wattage	Kelvin	Board Lumens	CRI	Code	Lamp	Type	Lamp Base
L60	65	3000	11370	+90	IN4, IN6, IN8	Med	A-19	Medium 120V
L65	65	3500	11370	+90				
L64	65	4000	11370	+90				
L80	105	3000	15160	+90				
L85	105	3500	15160	+90				
L84	105	4000	15160	+90				
L120	157	3000	22740	+90				
L125	157	3500	22740	+90				
L124	157	4000	22740	+90				

Universal Voltage unless otherwise specified.  
Contact factory for availability of other lamp configurations.

