

# DEMI

## Exterior Pendant






9777 Reavis Park Drive  
St. Louis, MO 63123  
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

### GENERAL SPECIFICATION

- LED:** High efficiency mid-power LEDs.
- LED Dimming:** Standard 1% 0-10V dimming.
- Listing:** ETL listed for wet locations.
- Canopy:** Matches fixture finish. Hanger 3 includes 10.125" dia by 2.625" H spinning.
- Driver:** Max remote driver installation distance 25ft from fixture body.
- Acrylic:** Acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat. Inner finish matches outer fixture finish.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER: GL-5360- E- BLK- 1- A 038					
MODEL NO.	LAMPING	FINISH	HANGER	OPTIONS	OVERALL HEIGHT
<b>GL-5360</b> 10lbs W 24" 4.5kg B 6" H 38"	<b>A.</b> 1LED30 <b>B.</b> 1LED35 <b>C.</b> 1LED40 <b>D.</b> 1LED30 <b>E.</b> 1LED35 <b>F.</b> 1LED40 <b>G.</b> 1LED30 <b>H.</b> 1LED35 <b>I.</b> 1LED40	<b>Standard:</b> <b>PC</b> -Powder Coat <b>BLK</b> -Black <b>BL</b> -Blue <b>GR</b> -Gray <b>LG</b> -Light Gray <b>BE</b> -Beige <b>PAB</b> -Antique Brass <b>PA</b> -Painted Aluminum <b>PTC</b> -Painted Copper <b>WH</b> -White <b>DBZ</b> -Dark Bronze <b>NSN</b> -New Satin Nickel <b>BRN</b> -Brown <b>RD</b> -Red <b>CH</b> -Champagne <b>RG</b> -Reed Green <b>SG</b> -Sungold <b>GM</b> -Gun Metal <b>POR</b> -Oil Rubbed Bronze <b>PG</b> -Pine Green <b>DO</b> -Deep Orange <b>PV</b> -Purple Violet <b>NB</b> -Navy Blue  <b>Textured Powder</b> <b>TLV</b> -Light Verdigris <b>TWH</b> -Textured White <b>TBL</b> -Textured Black <b>TS</b> -Textured Silver <b>TBZ</b> -Textured Bronze <b>TST</b> -Stone	<b>1. Stem Mount Remote Driver</b>  Drivers mounted remotely	<b>A.</b> No Options <b>EL.</b> Emergency LED Must be remotely mounted in a controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage.	Specify overall height in inches
<b>GL-5361</b> 10lbs W 30" 4.5kg B 7 7/16" H 40"			<b>3. Stem Mount Oversized Canopy</b>  Drivers mounted inside oversized canopy		
<b>GL-5362</b> 15lbs W 48" 7kg B 12" H 44"					

All Dimensions are nominal.

### Light Source Definition

Code	LED	Downlight Output		Kelvin	CRI
		Total Wattage	Delivered Lumens		
A	1LED30	15W	1695	3000	80
B	1LED35	15W	1695	3500	80
C	1LED40	15W	1695	4000	80
D	1LED30	26W	2906	3000	80
E	1LED35	26W	2906	3500	80
F	1LED40	26W	2906	4000	80
G	1LED30	39W	4359	3000	80
H	1LED35	39W	4359	3500	80
I	1LED40	39W	4359	4000	80

Universal Voltage unless otherwise specified.  
Fixture tested with white inner finish. Non-white inner finishes will reduce lumen output.