

FESTIVAL

Interior ADA Sconce




9777 Reavis Park Drive
St. Louis, MO 63123
800.331.2425 or 314.631.6000

sales@glighting.com www.glighting.com

GENERAL SPECIFICATION

- LED:** High efficiency +90CRI mid-power LEDs are field serviceable.
- LED Dimming:** Standard 1% 0-10V dimming. TRIAC, DALI, or DMX available upon request. Integral driver.
- Body:** Spun .050 aluminum or 18ga steel.
- Acrylic:** Seamless acrylic is UL-94 HB Flame Class rated.
- Finish:** Highly durable oven cured no VOC premium powder coat.
- Modifications:** Consult factory for lamping options.
- Surge Protection:** External surge protector provided as standard.



SAMPLE CATALOG NUMBER:					
GL-4110-		L15-	W-	SN-	A
MODEL NO.	LAMPING	ACRYLIC	FINISH	OPTION(S)	
GL-4110 W in 14 1/2" mm 370 H in 7 1/4" mm 185 5lbs 2.3kg D in 3 3/4" mm 95	L10. 1LED30 L15. 1LED35 L14. 1LED40	Standard: W. White Opal Optional: S. Satin White Acrylic is UL-94 HB Flame Class rated.	Standard: Powder Coat BLK- Black BL- Blue GR- Gray LG- Light Gray BE- Beige PAB- Antique Brass PA- Painted Aluminum PTC- Painted Copper WH- White DBZ- Dark Bronze NSN- New Satin Nickel BRN- Brown RD- Red CH- Champagne RG- Reed Green SG- Sungold GM- Gun Metal POR- Oil Rubbed Bronze PG- Pine Green DO- Deep Orange PV- Purple Violet NB- Navy Blue Textured Powder TLV- Light Verdigris TWH- Textured White TBL- Textured Black TS- Textured Silver TBZ- Textured Bronze TST- Stone	A. No Options EL. Emergency LED Remote mount up to 10' from light source in controlled environment with an area temperature range of 32°-131°F. Specify 120 or 277 voltage. L. Perforated Top Lens Painted white perforated metal top lens. TL. Acrylic Top Lens White acrylic top lens.	
GL-4111 W in 21 3/4" mm 550 H in 10 3/4" mm 275 7lbs 3.2kg D in 4" mm 100	L10. 1LED30 L15. 1LED35 L14. 1LED40				

All dimensions are nominal.

Light Source Definition

Code	Total Wattage	Rated CRI	Rated Life Hrs	Board Lumens	Kelvin
L10	13	+90	50000	1895	3000
L15	13	+90	50000	1895	3500
L14	13	+90	50000	1895	4000

Universal Voltage unless otherwise specified.
Contact factory for availability of other lamp configurations.

